

PERFORMANCE SPECIFICATION

LOGISTICS MANAGEMENT INFORMATION

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE.

1.1 Scope. This specification describes information required by the government to perform acquisition logistics management functions. The principle focus of this specification is on providing the DOD with a contractual method for acquiring support and support-related engineering and logistics data from contractors. The DOD uses this data in-house in existing DOD materiel management processes such as those for initial provisioning, cataloging, and item management. Data products intended primarily for in-house use by the contractor during his/her own design process or those developed internally by the DOD are beyond the scope of this document. Depending on specific program requirements, this information may be in the form of summary reports, a set of specific data products, or both. This specification identifies content requirements for information summaries and format requirement for data products. It may be used on all system/end item acquisition programs. The contractor may, and is encouraged to, suggest alternative means of satisfying requirements of this specification to make information more readily available and to utilize more efficient business practices. The mechanics of delivery (e.g., electronic data interchange, hard copy, etc.) are not within the scope of this specification and should be addressed separately. Data entry media, storage, and maintenance procedures are left to the contractor.

AMSC A7217

FSC ALSS

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

and Accounting Procedures

NAVSUP PUB 485 Afloat Supply Procedures

(Copies of specifications, standards, drawings, and other government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.3 Non-Government Publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

IEEE 200-75 Electrical and Electronics Parts and Equipment; Reference Designations for

(Non-government standards and other publications are normally available from the organizations that prepare or distribute the documents. The IEEE 200-75 is available from the Institute of Electrical and Electronics Engineers, 445 Hoes Lane, P.O. Box 1331, Piscataway, NJ 08855-1331. These documents also may be available in or through libraries or other informational services.)

2.4 Order of Precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS.

3.1 General. Logistics Management Information (LMI) is acquired to provide item sustainment data on a materiel system and information needed for planning, assessing program status, and program decisions. Before requirements of this specification are imposed, other commercial equivalent products or processes which satisfy government information needs will be considered. Contractor shall ensure that information provided under this specification is coordinated with the data requirements of other program elements to eliminate inconsistencies between deliverables.

3.2 Product Requirements.

3.2.1 Supportability Analysis Summaries. The Supportability Analysis Summaries (SAS) provide information for planning, assessing program status, and decision making by the government relative to various logistics disciplines. Appendix A describes the general requirements for each summary. The SAS shall contain information identified on the worksheets (figure 1).

3.2.1.1 SAS Level of Detail. The contractor shall provide SAS in the format and to the level of detail specified on contract.

3.2.1.2 SAS Current Design Configuration. The contractor shall provide SAS information which reflects current design configuration.

3.2.2 LMI Data Products. The data definitions, edits, and data formats described in appendix B shall be adhered to by the contractor in delivering the data. The worksheet (figure 2) shall be used to identify the required data products.

3.2.2.1 Data Product Level of Detail. Contractor shall provide data to the level of detail specified in the contract.

3.2.2.2 Data Product Current Design Configuration. Contractor shall provide data which reflects the current design configuration.

4. VERIFICATION.

4.1 General. The SAS and LMI Data Products will be verified by the government.

4.2 Supportability Analysis Summaries.

4.2.1 SAS Level of Detail. Contractor's summaries will be verified by the government to ensure they reflect the required level of detail as specified in the contract. Verification criteria for level of detail shall be specified in the contract.

4.2.2 SAS Accuracy Verification. Contractor's summaries will be verified by the government to ensure they accurately reflect the current design configuration. Verification criteria for summaries accuracy shall be specified in the contract.

4.3 LMI Data Products.

4.3.1 Data Product Level of Detail. Contractor's data will be verified by the government to ensure that it is documented to the level of detail specified in the contract. Verification criteria for level of detail shall be specified in the contract.

4.3.2 Data Product Accuracy Verification. Contractor's data will be verified by the government to ensure that it accurately reflects the current design configuration. Verification criteria for data accuracy shall be specified in the contract.

5. PACKAGING.

5.1 General. Packaging of the LMI Data Products is not applicable to this specification.

6. NOTES.

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended Use. This specification contains requirements which are applicable to the acquisition of military systems and equipment. The acquisition logistics management information should be in sufficient detail to allow for program decision making, assessing program status, planning, and ultimately item sustainment. The detail required of this information should be based on program specifics such as, but not limited to, life cycle phase, type of program, hardware complexity, operations and support concept, and degree of program control.

6.2 Issue of DODISS. When this specification is used in acquisition, the applicable issue of the DODISS must be cited in the solicitation.

6.3 Consideration of Data Requirements. This specification is cited in DOD 5010.12-L, Acquisition Management Systems and Data Requirements Control List (AMSDL), as the source document for the following Data Item Description (DID). When it is necessary to obtain the data, the applicable DID must be listed on the Contract Data Requirements List (DD Form 1423), except where the DOD Federal Acquisition Regulations Supplement exempts the requirement for a DD Form 1423.

<u>DID Number</u>	<u>DID Title</u>
DI-ALSS-81529	Logistics Management Information (LMI) Data Product(s)
DI-ALSS-81530	Logistics Management Information (LMI) Summaries

The above DIDs were current as of the date of this specification. The current issue of the AMSDL must be researched to ensure that only current and approved DIDs are cited on DD Form 1423.

6.4. Acronyms. The acronyms used in this specification are defined in appendix C.

6.5 Definitions. The data definitions for the interface part of this specification are defined in the data dictionary appendix C of this specification. In addition, for the purposes of this specification, the following definitions shall apply:

6.5.1 Assembly. A number of parts or subassemblies, or any combination thereof, joined together to perform a specific function and capable of disassembly (e.g., power shovel-front, fan assembly, audio frequency amplifier). NOTE: The distinction between an assembly and subassembly is determined by the individual application. An assembly, in one instance, may be a subassembly in another where it forms a portion of an assembly.

6.5.2 Attaching part. An item used to attach assemblies or parts to the equipment or to each other.

6.5.3 Component. An assembly or any combination of parts, subassemblies, and assemblies mounted together normally capable of independent operation in a variety of situations.

6.5.4 Contractor. Contractor may consist of industry or a government activity under the terms of a contract.

6.5.5 Design Change. An approved engineering change incorporated into the end item which modifies, adds to, deletes, or supersedes parts in the end item.

6.5.6 End Item. A final combination of end products, component parts/materials which is ready for its intended use, e.g., ship, tank, mobile machine shop, aircraft, receiver, rifle, or recorder.

6.5.7 Hardware Breakdown. A breakdown accomplished by sequencing all parts comprising the end item in a lateral and descending "family tree/generation breakdown." This breakdown shall consist of the end item, including all components, listing every assembly, subassembly, and parts which can be disassembled, reassembled/replaced. All parts are listed in their relation to the end item, component, assembly, or installation system in which they are contained and to their own further sub-subassemblies and parts. This relationship is shown by means of an indenture code.

6.5.8 Part. One piece, or more than one piece joined together, which are not normally subject to disassembly without destruction or impairment of designed use.

6.5.9 Repair Part. Material capable of separate supply and replacement which is required for the maintenance, overhaul, or repair of a system, equipment, or end item. This definition does not include support equipment, but does include repair parts for support equipment.

6.5.10 Spares. Articles identical to or interchangeable with repairable items which are procured for support of a system, over and above the quantity needed for initial assembly of the system.

6.5.11 Subassembly. Two or more parts which form a portion of an assembly or a component replaceable as a whole, but having a part or parts which are individually replaceable (e.g., gun mount stand, window recoil mechanism, floating piston, telephone dial, mounting board with mounted parts, power shovel dipper stick).

6.5.12 Support Equipment. "Support Equipment" is that equipment required to make an item, system, or facility operational in its intended environment. This includes all equipment required to maintain and operate the item, system, or facility including aerospace ground equipment and ground equipment.

6.5.13 Support Items. Items subordinate to or associated with an end item, i.e., spares, repair parts, and support equipment.

6.6 Subject Term (Key Word) Listing. Subject keywords allow identification of this document during retrieval searches.

LMI
Provisioning
Support Equipment
Item Management
Supportability
Supportability Analysis Summaries
Maintenance Planning
Repair Analysis
Support and Test Equipment
Supply Support
Manpower, Personnel, and Training
Facilities
Packaging, Handling, Storage, and Transportation
Post Production Support

6.7 Guidance.

6.7.1 Data Organization. The DOD has a number of standard data systems for wholesale materiel management which require data in a specific format. The contractor may interface directly with the customer data systems. An indented structure, with requiring authority approval, should be utilized for summaries and data products where required. The structure should depict relationships between assemblies, components, and other assemblies.

6.7.2 LMI Development. The contractor should suggest to the government the most effective method of LMI development, delivery, and eliminating unnecessary intermediate steps or deliverables.

6.8 Electronic Delivery of LMI. Electronic data interchange, online access, and all other automation issues are outside the scope of the MIL-PRF-49506, LMI and must be addressed separately using other appropriate documents such as MIL-STD-1840, Automated Interchange of Technical Information.

CONCLUDING MATERIAL

Custodians:
Army - TM

Preparing Activity:
Army - TM

(Project No. ALSS-0003)

Review Activities:
Navy - AS, MC
Air Force - 10
Miscellaneous DOD/NASA - NS, DC

MIL-PRF-49506
APPENDIX A

SUPPORTABILITY ANALYSIS SUMMARIES

A.1 SCOPE.

A.1.1 Scope. The following reports shall consist of information required for the requiring authority to conduct logistics planning and analysis, influence program decisions, assess design status, and verify contractor performance. Several information summaries are presented as examples of other useful support information that DOD managers may want to request from a contractor. These are not all inclusive or exclusive and are intentionally described in general terms to encourage maximum contractor flexibility. The content of the summaries is not limited to information and data products cited in the LMI specification. Content of the summaries should be specified on Supportability Analysis Summaries Worksheet (figure 1). Data not included in appendix B shall be defined on the worksheet (figure 1). The individual requirements should be taken into consideration when requesting these types of summaries. They can be delivered as stand alone reports or as an integral part of other systems engineering documentation. Requirements for these summaries shall be coordinated with data requirements of other program functional elements to minimize redundancies and inconsistencies. The following paragraphs describe report content in general terms. Specific content of each summary will be specified in the contract. Government and contractor should hold open dialogues to establish a format which both can use. Contractor format is acceptable when approved by the government. This appendix is a mandatory part of this specification.

A.2 Maintenance Planning. These summaries provide maintenance planning information to the government that may be used to develop initial fielding plans for the end items support structure. These summaries may also be used to verify that the maintenance actions and support structure are aligned with the government's requirements and maintenance concept. The information contained within these summaries are associated with repairable items to the level of detail specified on contract. The repairable items should be identified within the hierarchy of the end item broken down by an agreed upon configuration control method. It should identify all preventive and corrective maintenance actions along with the required spares and support equipment. These summaries should also provide supporting information justifying the need for each maintenance action, e.g., elapsed time of maintenance actions; task frequency; failure rate of an item; Mean Time To Repair an item; and an item's man-hour allocation by maintenance action and level.

A.3 Repair Analysis. These summaries provide the government with conclusions and recommendations of the maintenance repair analysis. The government may verify the conclusions and recommendations by utilizing contractor's inputs to perform an in-house analysis. These summaries may also be used by the government to develop initial fielding plans for the end item's support structure. The conclusions may include actions and recommendations for influencing the system design; a listing of which items should be repaired and which should be discarded. These summaries may identify for each item being repaired the level of maintenance at which the repair should be performed and associated costs. These summaries may identify for the system support structure, the operational readiness achieved, and the placement and allocation of spares, support equipment, and personnel.

These summaries may also include other information for the analysis performed, e.g., a listing of the input data and their corresponding values and sources of the data; operational scenario modeled; assumptions made; constraints and noneconomic factors imposed on the system; maintenance alternatives considered; the analytical method and model used to perform the economic evaluations; and discussion of the sensitivity evaluations performed and results obtained.

MIL-PRF-49506
APPENDIX A

A.4 Support and Test Equipment. These summaries provide data necessary to register, or verify the registry of, the support or test equipment in the government's inventory. They may provide details of the Test Measurement and Diagnostic Equipment (TMDE) calibration procedures, technical parameters, and any piece of support equipment needed to support the required support equipment.

A.5 Supply Support. These summaries provide the government with information on static and application related hardware information which may be used to determine initial requirements and cataloging of support items to be procured through the provisioning process. These summaries may include the identification of the system breakdown, maintenance coding, maintenance replacement factors, overhaul rates, roll-up quantities, design change information, and associated technical manuals, as applicable. These summaries may show information on different categories of provisional items such as long lead items, bulk items, tools and test equipment, etc. They may also allow for review of Provisioning List Item Sequence Number (PLISN) assignment or cross referencing PLISNs with reference numbers.

A.6 Manpower, Personnel, and Training. These summaries provide information to the government so it can establish training plans and ensure manpower and personnel constraints are met. The information contained within this report should identify items' corrective and preventive maintenance tasks, operations tasks, manpower estimates for each task by maintenance level, personnel skills required to perform the maintenance tasks, and any training required to allow these tasks to be performed. The information contained within this area is associated with items to the level of detail specified on contract. The items should be identified within the hierarchy of the end item broken down by an agreed upon configuration control method.

A.7 Facilities. These summaries identify the facilities required to maintain, operate, train, and test an item. The facilities may be organizational, intermediate, or depot maintenance, training, mobile and test facilities. The summary information contained within shall help plan for any modification to an existing facility or development of a new facility. The information shall be associated with repairable items to the level of detail specified in the contract. The repairable items should be identified within the hierarchy of the end item broken down by an agreed upon configuration control method. Data provided must be in compliance with all DOD and national health, life, and environmental codes. National standards and terminology used by the construction industry for civil, electrical, mechanical, etc., specialties should be used.

A.8 Packaging, Handling, Storage, and Transportation. These summaries identify packaging, handling, and storage requirements. They also provide information relevant to the development of a transportability analysis report. The information contained within this area is associated with the reference number and Commercial And Government Entity (CAGE) to the level of detail specified on contract. The information contained within this area is associated with repairable items to the level of detail specified on contract. The repairable items should be identified within the hierarchy of the end item broken down by an agreed upon configuration control method.

A.9 Post Production Support. The purpose of these summaries is to analyze life cycle support requirements of the new system/equipment/software prior to closing of production lines to ensure the system/equipment/software's remaining life. These summaries identify support items associated with the system/equipment/software that will present potential problems due to inadequate sources of supply, support capability, or modification after shutdown of production lines. They also identify alternative solutions for anticipated support difficulties during the remaining life of the system/

equipment/software. General topics that may also be addressed in these summaries are manufacturing, repair centers, data modifications, supply management, configuration management, and other related areas.

SUMMARY TITLE:																								
SPECIFIC INSTRUCTIONS:																								
DATA IN LMI SPECIFICATION (Please provide the data product title): <table border="1"><tr><td>_____</td><td>_____</td><td>_____</td></tr><tr><td>_____</td><td>_____</td><td>_____</td></tr><tr><td>_____</td><td>_____</td><td>_____</td></tr><tr><td>_____</td><td>_____</td><td>_____</td></tr><tr><td>_____</td><td>_____</td><td>_____</td></tr><tr><td>_____</td><td>_____</td><td>_____</td></tr><tr><td>_____</td><td>_____</td><td>_____</td></tr><tr><td>_____</td><td>_____</td><td>_____</td></tr></table>	_____	_____	_____	_____	_____	_____	_____	_____	_____	_____	_____	_____	_____	_____	_____	_____	_____	_____	_____	_____	_____	_____	_____	_____
_____	_____	_____																						
_____	_____	_____																						
_____	_____	_____																						
_____	_____	_____																						
_____	_____	_____																						
_____	_____	_____																						
_____	_____	_____																						
_____	_____	_____																						
DATA NOT IN LMI SPECIFICATION (Please provide the data product title, its definition and its format):																								
SUMMARY LAYOUT (if applicable): Government Provided <input type="checkbox"/> Contractor Provided <input type="checkbox"/>																								

FIGURE 1 - WORKSHEET 1 - SUPPORTABILITY ANALYSIS SUMMARIES

LMI DATA PRODUCTS DICTIONARY

B.1 SCOPE.

B.1.1 Scope. This appendix provides the definitions for the LMI data products and their associated names. This appendix is a mandatory part of this specification.

B.2 Sections. The LMI Data Product Dictionary contains some or all of the following entries. When a standard data acronym applies, this is also listed in this section.

- a. Data Product Dictionary Number (DPD #)
- b. Data title with acronym
- c. Field format
- d. Definition
- e. Data item(s)
- f. Data code(s)
- g. Associated name(s)

B.2.1 Format. The general format for the DPD is as follows:

DPD#	DATA TITLE (ACRONYM)	FIELD FORMAT
	DATA DEFINITION	
	DATA ITEM(S)	DATA CODE(S)
	ASSOCIATED NAME(S)	

Example of actual entry:

0050 BASIS OF ISSUE (BOI) 15 X - -

This field is composed of the following four subfields:

- a. Quantity Authorized (QTY-AUTH) 5 N R -

The quantity of an item (special tool) authorized for the end item density spread or for the unit level specified.

- b. End Item 8 X L -

The density spread of the end items.

- c. Level 1 A F -

A code which indicates the unit level authorized for the QTY-AUTH.

QTY-AUTH per lettered company	A
QTY-AUTH per battalion (BN) headquarters (HQ) when BN has a service (SVC) company	B
QTY-AUTH per HQ of units above BN level	C
QTY-AUTH by BN and brigade (BDG) type HQ (except when BN or BDG has SVC company)	D

MIL-PRF-49506
APPENDIX B

QTY-AUTH by SVC battery/company	E
QTY-AUTH by numbered battery/company and similar	F
HQ performing ORG maintenance for other units	

d. Control 1 N F -

A code 1-9 used for sequencing and controlling BOI entries.

B.2.2 Definition of terms.

B.2.2.1 DPD#. A sequentially assigned number to each data product in the dictionary for use in locating and referencing it throughout the dictionary.

B.2.2.2 Data title. The noun phrase name used to identify the data. Sufficient adjectival modifiers are used with the noun name to ensure title uniqueness.

B.2.2.3 Field format. A specification for the length, type, positional justification, and decimal placement of a data field, or subfield thereof, as described below:

a. Length. The number of character positions in the data. In the event the length is variable, the maximum length is specified.

b. Type. A specification of the character type, wherein:

"A" specifies that all characters of the data entry are upper case alphabetical.

"N" specifies that all characters of the data entry are numerical.

"X" specifies that characters of the data entry are upper case alphabetical, numerical, special, or any combination thereof.

"D" specifies that characters of the data entry are numerical with floating decimal. Decimals may be entered as required or exponentially, e.g., "0.0000325" or "3.25E-5".

c. Justification. Specifies from which side of the field the characters of the data are entered. Those starting at the left are left justified (L), those starting at the right are right justified (R). Those which always occupy the entire field are fixed (F).

d. Decimal Placement. Specifies the number of character positions to the right of the assumed decimal point when the data is numeric in all character positions. "AS" means "As Specified" and the detailed instructions will indicate the location of decimal points.

e. A dash (-) used in any column signifies that it is not applicable.

B.2.2.4 Data Definition. A narrative definition of the data in sufficient detail to present a clear and complete understanding of the precise data or element of information that the data represents.

B.2.2.5 Data item. One of a set of descriptive items of information or values that apply to a data product.

B.2.2.6 Data code. One or more alphabetical, numerical, special characters, or any combination thereof, that represent a data item. A code is used instead of the data item itself, in order to conserve space.

Note 1: In some cases, a position left blank counts as a data code signifying

MIL-PRF-49506
APPENDIX B

some particular data item value as specified in the dictionary.

Note 2: When data items and data codes are too voluminous to be included in this document, reference is made to items and codes in another document.

B.2.2.7 Associated name. A unique modifier of a data title which describes the use/application of the data.

MIL-PRF-49506
APPENDIX B

LMI DATA PRODUCT DICTIONARY

0010 ALLOWANCE ITEM CODE (AIC) 2 X F -

Consists of two subfields: Allowance Type and Allowance Code.

a. Allowance Type 1 A F -

A code which indicates the type of item.

Basic issue item category code (Army)	A
Allowance note code (Navy)	B
Technical override (TOR) code (Navy)	C
Allowance factor code (Air Force)	D
Stockage list category (Marine Corps)	E

b. Allowance Code 1 X F -

A code which further defines and categorizes the allowance type.

(1) When an Allowance Type code of "A" is specified, one of the following codes must be used for Allowance Code:

Basic issue item	A
Component of end item	C
Expendable/durable supplies and materials	D
Additional authorization list items (modified table of organization and equipment)	E
Additional authorization list items (other)	F

(2) When an Allowance Type code of "B" is specified, one of the following codes must be used for Allowance Code:

- Indicates an operating space item regardless of vessel type. The Stock Number Sequence List (SNSL) reflects a quantity for each application. 1
- REFER TO YOUR ALLOWANCE PARTS LIST (APL) to determine if the repair part is required (since exceptions are annotated on the APL when the repair part may not be required) or where a choice must be made to select the correct repair part. 2
- Represents the superseding repair part due to redesign or material change. The superseded stock number appears as alternate information in part III, section D, of the Coordinated Shipboard/Allowance List (COSAL). The superseded item, presently on board, can be used without adverse effect to the component. If the superseded item is presently on board, utilize the stock under the superseded number before ordering deficiencies. 3
- An item with an NSN for bulk material that is to be used in the fabrication of the item listed in the parts list. Requisition as required. 4
- Denotes CLASSIFIED PART and should be requisitioned and stored IAW current security regulations. 5
- An RSS (Ready Service Spare) which will appear in the COSAL section III CR of the SNSL. This item may also appear in section IIIA of the SNSL as a storeroom item for this APL application if anticipated usage warrants 6

MIL-PRF-49506
APPENDIX B

backup support.

Denotes an item that is to be requisitioned and stowed IAW confidential instructions. This note applies to operating frequency control crystals allowance.	7
Indicates an accessory component/components applicable to a parent equipment.	8
Item(s)/part(s) for which only the Commanding Officer or his designated representative is specifically responsible for the physical custody and safekeeping thereof.	9
Represents an item that has been coded to deviate from the NORMAL MAINTENANCE POLICY expressed by the Lead APL. The responsible hardware command authorizing this deviation will be annotated in the characteristic portion of the APLs.	A
Indicates that the ORDNANCE alteration has been performed and repair parts are not required.	C
Applicable to S/O/S (SHIPALT/ORDALT/SPALT) items, indicates the quantity by which the affected APL population of the item has been decreased after accomplishment of the S/O/S.	D
Indicates that a Technical Override (TOR) or Planned Maintenance Requirement (PMR) is included in the allowed quantity.	E
Indicates that note codes 3 and E, above, apply to the item.	F
Indicates that note codes 2 and E, above, apply to the item.	G
Represents an item listed on Allowance Equipage Lists (AEL) to provide technical information only and is not an authorized allowance.	H
Indicates that note code 1 or X and note code 2 both apply to the item.	J
Represents a module required to execute approved maintenance planning which calls for identifying the fault or failed module through progressive/selective module substitution. Maintenance Assistance Modules (MAM) will be included as an Operating Space Item (OSI) in the COSAL, section III CF of the Stock Number Sequence List (SNSL). The item may also appear in section IIIA of the SNSL as a storeroom item for this APL application if anticipated usage warrants backup support.	N
Represents the preferred item in a situation where two or more items are interchangeable. The alternate nonpreferred item(s), if presently on board, may be utilized to satisfy the allowance requirement; however, when a shortage exists, the preferred item of stock should be requisitioned. The alternate item of stock will appear in the Preferred-to-Alternate Substitute Cross-Reference List.	S
Select at test. All NSNs required for the selection are listed for each circuit symbol. Item needed must be selected from among the listed NSNs based on equipment operating requirements. A suffix has been assigned to the circuit symbol for identification.	T

MIL-PRF-49506
APPENDIX B

Variable. See the characteristics portion of APL.	V
APL will state: NSN...has been canceled -- it cannot be procured. When part fails, replace with the next higher assembly.	W
Indicates an operating space item. The SNSL quantity is established by the highest single application quantity in all of the items X code applications.	X
On Board Repair Part (OBRP) Kits. OBRP quantities are included in the APPL (Application) column of section B and the QTY in one equip/comp columns of section A. These kits should be retained as OBRP even if not listed in the COSAL SNSL/Integrated Stock List (ISL).	Z
(3) When an Allowance Type code of "C" is specified, one of the following codes must be used for Allowance Code.	
Operational Availability Override Requirement. Indicates that the Allowance Override quantity (C007A) finite quantities determine the allowance quantity for the Operational Availability computational math model. For a given item, a comparison between the single highest "A" quantity, other overrides, the sum of all PMR, and the computed demand-based quantity, is made and the highest single quantity is selected as the authorized allowance.	A
Critical Candidate. Identifies items to be stored as higher supply echelons (see Note 1 below).	C
Disapproved Technical Override. TOR reviewed and disapproved by the cognizant Hardware Systems Command for .25 Fleet Logistic Support Improvement Program (FLSIP) computations, under .15 computation item allowance determined by the C007A finite quantities (see Note 2 below).	D
Early Supply Support (ESS). Indicates that the finite quantity in C007A is used in place of the quantity per allocation for allowance computation.	E
Approved TOR Mission Override. TOR accepted to support primary mission. The C007A finite quantity determines the allowance for a particular item.	M
Planned Maintenance Requirement (PMR). Indicates that the C007A finite quantities for an item are additive across all applications, and the summarized PMR quantity determines the authorized allowance when compared with other overrides and the computed demand-based allowance.	P
Requisition as Required. Indicates that "AR" is printed in the quantity field for an item. Programs disregard quantities in C007A. "R" overrides all other populations for an item.	R
Safety Equipment. Specified C007A quantity is justified allowance to ensure safety and preserve life.	S

MIL-PRF-49506
APPENDIX B

Technical Override. Indicates that the highest finite C007A quantity for a given item is compared with the summarized PMR quantity, other override quantities, and the demand-based computed quantity, the highest of these quantities becomes the authorized allowance. Applies to .15 FLSIP only. T

Disapproved TOR. Justification reserved for future use. V

Operational Availability Underride. Indicates that the item population for this application is not used to determine allowance quantities. No finite quantity is loaded in C007A (used to exclude items from the Operational Availability model). Y

Zero Override. Indicates that the item population for this application is not used to determine allowance quantities. No finite quantity is loaded in C007A. Used to exclude items from FLSIP model. Z

NOTE:

1. An informational code designed to assist in the future selection of items to be stocked at higher echelons. Instructions for the use of this code will be provided by the requiring authority. C-coded items will be processed in the same manner as D-coded items.

2. D-coded items will still be considered as valid candidates for on-board stocking and can be included on allowances if other support criteria is met.

(4) When an Allowance Type code of "D" is specified, the requiring authority will specify the code to be used for Allowance Code.

(5) When an Allowance Type code of "E" is specified, one of the following codes must be used for Allowance Code:

Principal end item	A
Using unit responsible item	C
Supply system responsible item	D
Collateral Equipment	E

0020 ALLOWANCE ITEM QUANTITY 3 N R -

A quantity which is defined by the Allowance Item Code (0010).

0030 ALTERNATE INDENTURED PRODUCT CODE (AIPC) 3 N F -

A code used to allow documentation of multiple models of a system/equipment, or alternate design considerations of an item, using the same Indentured Product Code (IPC) breakdown.

Note: AIPC of zero zero zero "000" will always be used as the basic system. There are no blanks allowed. AIPC's will be assigned from 001 to 999 in ascending order.

ALTERNATE IPC - UUT. An AIPC of the Unit Under Test (UUT).

0040 AUTOMATIC DATA PROCESSING 1 N F -
EQUIPMENT CODE

MIL-PRF-49506
APPENDIX B

A code which identifies an item of Automatic Data Processing Equipment (ADPE) or containing ADPE, regardless of Federal Supply Classification (FSC) to provide visibility for compliance with unique manager requirement established for ADPE by Public Law 89-306. Applicable codes are contained in DOD 4100.39-M.

0050 BASIS OF ISSUE (BOI) 15 X - -

This field is composed of the following four subfields:

a. Quantity Authorized (QTY-AUTH) 5 N R -

The quantity of an item (special tool) authorized for the end item density spread or for the unit level specified.

b. End Item 8 X L -

The density spread of the end items.

c. Level 1 A F -

A code which indicates the unit level authorized for the QTY-AUTH.

QTY-AUTH per lettered company	A
QTY-AUTH per battalion (BN) headquarters (HQ) when BN has a service (SVC) company	B
QTY-AUTH per HQ of units above BN level	C
QTY-AUTH by BN and brigade (BDG) type HQ (except when BN or BDG has SVC company)	D
QTY-AUTH by SVC battery/company	E
QTY-AUTH by numbered battery/company and similar HQ performing ORG maintenance for other units	F

d. Control 1 N F -

A code 1-9 used for sequencing and controlling BOI entries.

0060 CALIBRATION AND MEASUREMENT REQUIREMENTS 1 A F -
SUMMARY RECOMMENDED

A field depicting whether or not a Calibration and Measurement Requirements Summary is recommended. Codes are as follows:

Calibration and Measurement Requirements Summary (CMRS) recommended	Y
Not recommended for CMRS	N

0070 CALIBRATION INTERVAL 2 N R -

The frequency in months between which a support/test equipment must be calibrated in order to operate within specified tolerances.

0080 CALIBRATION ITEM 1 A F -

A single position code indicating that the item recommended is itself an item of calibration equipment.

Item is a calibration item	Y
Item is not a calibration item	N

0090 CALIBRATION PROCEDURE 20 X L -

MIL-PRF-49506

APPENDIX B

The technical manual/order number or instructions that specifies the calibration procedure. For items of TMDE that have an approved method of support, list the applicable military department approved calibration procedure, technical order, or maintenance technical order in the item name block.

0100 CALIBRATION REQUIRED 1 A F -

A single position code indicating whether the support/test equipment recommended or procured requires calibration.

Calibration required Y
Calibration not required N

0110 CALIBRATION TIME 5 N R 1

The time, in hours, required to calibrate the support/test equipment.

0120 CHANGE AUTHORITY NUMBER 15 X L -

A number to uniquely identify an authority for an engineering change. The change authority and a numbering sequence will be provided by the requiring authority.

0130 CLEANING AND DRYING PROCEDURE 1 X F -

A code which identifies the procedure for removing soil from parts and the procedure to accomplish the subsequent drying of the cleaned part. For applicable codes, see MIL-STD-2073.

0140 COMMERCIAL AND GOVERNMENT ENTITY (CAGE) CODE 5 X F -

A five-character code assigned by the Defense Logistics Services Center (DLSC) to the design control activity or actual manufacturer of an item as contained in the Cataloging Handbook H4/H8 Series.

CAGE CODE - ADAPTER INTERCONNECTOR DEVICE. A CAGE of the adapter interconnector device used in conjunction with the support equipment (SE).

CAGE CODE - ARN. A CAGE of the additional reference number.

CAGE CODE - ARN ITEM. A CAGE of the primary item reference number.

CAGE CODE - ARTICLES REQUIRING SUPPORT. A CAGE of the article requiring support.

CAGE CODE - ATE. A CAGE of the automated test equipment.

CAGE CODE - CATEGORY III SE. A CAGE of the SE which measures the SE Unit Under Test (UUT).

CAGE CODE - CTIC. A CAGE associated with the CTIC.

CAGE CODE - PACKAGING DATA PREPARER. A CAGE of the packaging data preparer.

CAGE CODE - SUPPORT EQUIPMENT. A CAGE of the SE under analysis.

CAGE CODE - TEST PROGRAM SETS. A CAGE of the test program sets used in conjunction with the SE.

MIL-PRF-49506
APPENDIX B

CAGE CODE - UUT. A CAGE of the UUT.

0150 CONTRACTOR FURNISHED EQUIPMENT/ 1 A F -
GOVERNMENT FURNISHED EQUIPMENT (CFE/GFE)

A single-position code indicating the contractor's recommendation for supply action.

Contractor Furnished	C
Government Furnished	G

0160 CONTRACTOR RECOMMENDED 1 A F -

A code to signify whether or not the corresponding requirements are contractor recommended. Codes are as follows:

YES	"Y"
NO	"N"

CONTRACTOR RECOMMENDED - DDCC. Identify the requirements for the design data category code and if there contractor recommended.

CONTRACTOR RECOMMENDED - IRCC. Identify the requirements for the integrated logistics support requirement category code and if they are contractor recommended.

0170 CONTRACTOR TECHNICAL INFORMATION CODE 2 A - -
(CTIC)

A code which indicates specific information regarding the technical process/data required to procure or produce the support item.

a. The first position of the CTIC contains a Breakout Recommendation Code. For a Navy acquisition program, the only applicable code is "C", which does not relate to first position code "C" of this DD.

Recommended for Breakout	A
Not Recommended for Breakout - Safety	B
Not Recommended for Breakout - Warranty	C
Not Recommended for Breakout - Unstable Design	D
Not Recommended for Breakout - Value Added	E
Not Recommended for Breakout - Other/Combination	F

Note: If code "F" is used, remarks block of provisioning list will contain elaboration.

b. Codes for the second position are as follows:

Source(s) are specified on "Source Control", "Altered Item", or "Selected Item" drawings/documents. (The contractor shall furnish a list of the sources with this code as additional reference numbers and CAGEs.)	B
--	---

Requires engineering source approval by the design control activity in order to maintain the quality of the part. An alternate source must qualify IAW the design control activity's procedures, as approved by the cognizant government engineering activity.	C
--	---

There are no technical restrictions to competition.	G
---	---

MIL-PRF-49506
APPENDIX B

Produced from class 1A castings and similar type forgings. The process of developing and proving the acceptability of high-integrity casting and forgings requires repetitive performance by a controlled source. Each casting or forging must be produced along identical lines to those which resulted in initial acceptability of the part. The contractor shall furnish a list of known sources for obtaining casting/forgings with this code. K

Master or coordinated tooling is required to produce this part. This tooling is not owned by the government or, where owned, cannot be made available to other sources. The contractor shall furnish a list of the firms possessing the master or coordinated tooling with this code. M

Requires special test/inspection facilities to determine and maintain ultra-precision quality for function or system integrity. Substantiation and inspection of the precision or quality cannot be accomplished without such specialized test or inspection facilities. Other sources in industry do not possess, nor would it be economically feasible for them to acquire facilities. The contractor shall furnish a list of the required facilities and their locations with this code. N

The rights to use the data needed to purchase this part from additional sources are not owned by the government and cannot be purchased. P

A high reliability part under a formal reliability program. Probability of failure would be unacceptable from the standpoint of safety of that personnel/equipment. The cognizant engineering activity has determined that data to define and control reliability limits cannot be obtained, nor is it possible to draft adequate specifications for this purpose. Continued control by the existing source is necessary to ensure acceptable reliability. (The contractor shall identify the existing source with this code as additional numbers and CAGEs.) V

The design of this part is unstable. Engineering, manufacturing, or performance characteristics indicate that the required design objectives have not been achieved. Major changes are contemplated because the part has a low process yield or has demonstrated marginal performance during tests or service use. These changes will render the present part obsolete and unusable in its present configuration. Limited acquisition from the present source is anticipated pending configuration changes. The contractor shall identify the existing source with this code as a reference/additional reference number and CAGE. Y

0180 CONTROLLED INVENTORY ITEM CODE 1 X F -

Codes which indicate the security classification, risk or pilferage controls for storage and transportation of DoD assets. For applicable

MIL-PRF-49506

APPENDIX B

codes, see DOD 4100.39-M.

0190 CRITICALITY CODE

1 A F -

A code which indicates that an item has been assessed and documented in the TDP as being technically critical by reason of tolerance, fit restrictions, application, nuclear hardness properties or characteristics which affects identification of the item.

The item has critical features such as tolerance fit restrictions or application. Nuclear hardness properties have not been determined. C

The item is a Flight Safety Critical Aircraft Part (FSCAP) and is specifically designed to be or selected as being nuclear hardened. E

The item is a FSCAP. F

The item does not have a critical feature such as tolerance, fit restrictions, or application. Nuclear hardness properties have not been determined. N

The item is specifically designed to be selected as being nuclear hard (i.e., it will continue to perform its designed function in an environment created by nuclear explosion). The item does not have other critical features. H

The item is specifically designed to be selected as being nuclear hard. In addition, the item has other critical features such as tolerance, fit restrictions, or application. M

The item does not have a nuclear hardened feature or any other critical feature such as tolerance, fit restrictions, or application. X

The item does not have a nuclear hardened feature but does not have other critical feature(s) such as tolerance, fit restrictions, or application. Y

0200 CUSHIONING AND DUNNAGE MATERIAL CODE

2 X F -

A code which identifies resilient material employed for the purpose of absorbing shock and preventing damage to the item or material used for preventing movement of the item within the package. For applicable codes, see MIL-STD-2073.

0210 CUSHIONING THICKNESS

1 X F -

A code which indicates the minimum thickness of material used to cushion the item. For applicable codes, see MIL-STD-2073.

0220 DEGREE OF PROTECTION CODE

1 A F -

A code to indicate the level of protection which the package requirement provides the item during shipment, handling, and storage. For code explanations, see MIL-STD-2073.

Level A A
Level B B

MIL-PRF-49506
APPENDIX B

Level C

C

0230 DEMILITARIZATION CODE (DMIL) 1 A F -

A code which indicates the degree of demilitarization required for an item. For applicable codes, see DOD 4100.39-M.

0240 DESCRIPTION/FUNCTION AND CHARACTERISTICS - - - -
OF SUPPORT EQUIPMENT

Narrative information about the operational characteristics of the SE, including minimum and maximum capabilities, of the selected support and test equipment or training device. Also includes information about specific operating and functional performance characteristics, corresponding tolerance accuracy, and design criteria necessary to satisfy functional requirements. Any critical or limiting performance characteristics that must be considered before substitution of a similar item must also be included. Narrative specifics might include equipment type; units of measurement; degrees of measurement; and parametric ranges and tolerances. If operational characteristics are classified, state so in this block. Information regarding material finish, fragility, service requirements, etc., shall be included. If the SE is a commercial item, state so in this block.

0250 DESIGN DATA CATEGORY CODE 1 A F -

Codes indicating the design data being considered, which are recommended or not recommended by the contractor or government. Codes are as follows:

SE Standardization	A
SE Specification	B
Design Engineering	C
Configuration Control	D
Reliability	E
Maintainability	F
Quality Assurance	G
Safety	H
Human Engineering	I
Test and Evaluation	J
Computer Resources	K
SE Illustration	L
Other	M

0260 DESIGN DATA PRICE 8 N R -

The total expected price, for budgetary planning, associated with contractor-recommended hardware/software design activities.

0270 END ITEM ACRONYM CODE (EIAC) 10 X L -

A code which uniquely identifies the system/equipment end item, but not the item designator. This code will be assigned by the requiring authority. It will remain constant throughout the item's life cycle (e.g., TOW, PATRIOT, Tomahawk, Sparrow, and ALCM).

0280 ESSENTIALITY CODE 1 N F -

A code to indicate the degree to which the failure of the part affects the ability of the end item to perform its intended operation.

Failure to this part will render the end 1

MIL-PRF-49506
APPENDIX B

	item inoperable.	
	Failure to this part will not render the end item inoperable.	3
	Item does not qualify for the assignment of code 1, but is needed for personnel safety.	5
	Item does not qualify for assignment of code 1, but is needed for legal, climatic, or other requirements peculiar to the planned operational environment of the end item.	6
	Item does not qualify for the assignment of code 1, but is needed to prevent impairment of or the temporary reduction of operational effectiveness of the end item.	7
0290	ESTIMATED PRICE	8 N R -
	An estimated cost associated with each contractor-recommended requirement for budgeting and planning.	
	ESTIMATED PRICE - DDCC. Estimated cost associated with the design data category code.	
	ESTIMATED PRICE - IRCC. Estimated cost associated with the integrated logistics support requirement category code.	
0300	FIGURE NUMBER	4 X R -
	A number assigned to identify a specific illustration contained in a manual.	
0310	FRAGILITY FACTOR	3 N R -
	The maximum force acceleration or deceleration, expressed in units of gravity (Gs) that can be applied to an item in its non-operating state without causing physical damage or change in its operational characteristics.	
0320	FUNCTIONAL ANALYSIS	- - - -
	A statement shall give, in technical and quantitative terms, a precise description of the function requiring support, including the specific operating critical and fundamental performance characteristics, corresponding tolerance or accuracy, and design criteria necessary. Also describe the required interval for performance of the function; required input and output characteristics and measurements; and environmental conditions under which the piece of SE is to be used.	
0330	FUNCTIONAL GROUP CODE	11 X L -
	An alphanumeric code used to identify a particular system, subsystem, component/assembly, or part of the system/equipment used for development of maintenance allocation charts, narrative technical manuals, and repair parts and special tools lists. Codes will be as specified by the requiring authority.	
0340	HARDNESS CRITICAL ITEM (HCI)	1 A F -

MIL-PRF-49506
APPENDIX B

A code which identifies an item at any assembly level which is mission critical and could be designed, repaired, manufactured, installed, or maintained for normal operation and yet degrade system survivability in a nuclear, biological, or chemical hostile environment, if hardness was not considered.

Hardness critical	Y
Not Hardness critical	N

0350 HARDWARE DEVELOPMENT PRICE 8 N R -

The estimated cost in dollars of hardware development of the SE. This price does not include the cost of deliverable hardware.

0360 HAZARDOUS CODE 1 A F -

A code which indicates whether the item is regulated or nonregulated. For regulated items, see Code of Federal Regulations (CFR) 49 and the United Nations Transport of Hazardous Goods. Hazardous Code is required by MIL-STD-2073.

Regulated hazardous in accordance with CFR 49	D
Nonhazardous item	N

0370 INDENTURE CODE 1 X F -

A code which illustrates a lateral and descending "family tree" relationship of each line item to and within the system or end item and its discrete components (units), assemblies and subassemblies, and sub-subassemblies, e.g., "A" for the system, "B" for the major system components, "C" for assemblies, "D" for subassemblies, etc.

a. Attaching Part/Hardware. Attaching part hardware shall be listed according to the following options as specified by the requiring authority:

Option 1. Indentured with a "Z" below the item it attaches.

Option 2. Indentured with a "Z" and listed as a bulk item within each appropriate level component where it appears.

Option 3. Indentured with a "Z" and listed as a bulk item at the end of the provisioning list.

Option 4. All parts indicated on drawing will be listed in the breakdown in proper indenture without specific identification that the parts are utilized as "attaching parts".

Option 5. Attaching hardware need not be listed.

b. Indenture for kits. When maintenance planning/practices require that a group of parts be replaced in one maintenance or overhaul operation, these items shall be listed as a kit IAW with one of the following options:

Option 1. Kits shall be assigned an indenture lower than the subassembly/assembly/component/end item for which it is used and parts of the kit shall be identified by entering an asterisk.

Option 2. The kit reference number shall be listed at the end of the subassembly/assembly/component/end item breakdown.

MIL-PRF-49506
APPENDIX B

Option 3. All kit parts shall be listed in the PPL in proper indenture without specific identification that the parts are kit components. The kit part number is to be listed as the last item of the applicable next higher assembly, end item/assembly/subassembly breakdown.

INDENTURE CODE - IPC. The indenture code of the IPC.

0380 INDENTURED PRODUCT CODE (IPC) 24 X L -

A code that represents the indentured product. The IPC will represent the system/equipment breakdown. The methods for IPC assignment may consist of physical, functional/physical, drawing number, etc.

INDENTURED PRODUCT CODE - UUT. An IPC of the Unit Under Test.

0390 INPUT POWER SOURCE 23 X - AS

The operating power requirements necessary for the TMDE to function and operate properly. They consists of the following subfields:

a. Operating Range 6 N - -

The voltage range which the TMDE requires to function properly. Subfields are:

(1) Minimum 3 N R -

The minimum voltage which the TMDE requires to function properly.

(2) Maximum 3 N R -

The maximum voltage which the TMDE requires to function properly.

b. Alternating Current/
Direct Current 1 A F -

A code indicating the type of voltage required to operate the Automatic Test Equipment(ATE)/TMDE, support/test equipment.

Alternating Current A
Direct Current D

c. Frequency Range 6 N - -

The number of periods or cycles, in hertz, for a given voltage or voltage range, which consists of following subfields:

(1) Minimum 3 N R -

The minimum frequency which the TMDE requires to function properly.

(2) Maximum 3 N R -

The maximum frequency which the TMDE requires to function properly.

d. Phase 1 N F -

The number of simultaneously applied AC voltage sources for a given voltage range.

MIL-PRF-49506
APPENDIX B

Single phase	1
Double phase	2
Triple phase	3

e. Watts 5 N R -

The unit of power equivalent to the current of one ampere flowing across a potential difference of one volt.

f. Percent Maximum Ripple 4 N R 2

The percent maximum ripple allowable of the output voltage of the power source available to operate the TMDE.

0400 INSTALLATION FACTORS OR OTHER FACILITIES - - - -

A narrative description identifying any considerations required for the installation of support and test equipment or training material, such as vibration and shock mounting requirements, special foundations, utilities connections, and environmental factors. Also, it includes any equipment necessary to install the item, e.g., cranes, hoists, lift trucks, transits, etc. When new or modified facilities are required to house the support, test equipment, or training materials. Facilities data may also be required.

0410 INTEGRATED LOGISTIC SUPPORT PRICE 8 N R -

The total cost associated with ILS deliverable recommendations made by the contractor.

0420 INTEGRATED LOGISTIC SUPPORT REQUIREMENTS CATEGORY CODE 1 A F -

Codes indicating the ILS requirements. Codes are as follows:

ILS plan	A
Supportability analysis	B
Maintenance planning	C
Interim support items list	D
Repair of repairables	E
Provisioning technical documentation	F
Master index of repairables	G
Calibration and Measurement Requirements Summary	H
Facilities data	I
Technical manuals	J
Maintenance requirements card	K
Instrument calibration procedures	L
Phased support plan	M
Component pilot rework/repair	N
Rework standard	O
New start	P
Training	Q
Contractor engineering and technical services	R
Packaging, handling, storage, and transportation	S
Other	T
Estimated total ILS price	U

0430 INTERCHANGEABILITY CODE 2 A F -

A code which indicates relationship of items.

MIL-PRF-49506
APPENDIX B

a. Signifies One-Way (OW) interchangeability as follows:

(1) When used for a change to the original item, means that the original item may be used until exhausted. OW

(2) When used for the replacement item, "OR" means that the new item may be used to replace the original item. OR

b. Signifies that the original item and replacement item are interchangeable with each other. TW

c. Signifies that the item is Not Interchangeable (NI) as follows:

(1) When used for the original item, NI means that the item is not interchangeable with the replacement item. NI

(2) When used for the replacement item, NR means that the replacement item is not interchangeable with the original item. NR

d. Signifies that the original item is interchangeable with the replacement item only if modified to the replacement item configuration and only in the new application. OM

e. Signifies that the original item is interchangeable in both the old and new application only if the original item is modified to the replacement configuration. TM

0440 INTERMEDIATE CONTAINER CODE 2 X F -

A code to identify a container which holds two or more unit packs of identical items. For applicable codes, see MIL-STD-2073.

0450 INTERMEDIATE CONTAINER QUANTITY 3 A F -
3 N R -

The quantity of unit packs contained in the Intermediate Container. For quantities over 999, see MIL-STD-2073.

0460 ITEM CATEGORY CODE (ICC) 2 X L -

A code which identifies a type of item and indicates categories into which support and test equipment, spares, repair parts, etc., may be divided. Program specific ICCs, not utilized in the following list, can be assigned if approved by the government authority.

Peculiar SE and tools not currently in the DOD inventory.	7
Peculiar SE (Other)	8
Peculiar tools	M
Peculiar test equipment	D
Peculiar handling equipment	1
Peculiar ATE	

Common SE and tools currently in the

MIL-PRF-49506
APPENDIX B

DOD inventory.	
Common SE (Other)	H
Common tools	4
Common test equipment	5
Common handling equipment	6
Common ATE	2
Common SE and tools currently in the DOD inventory but not assigned to a unit/ship.	
Common SE (Other)	G
Common tools	N
Common test equipment	P
Common handling equipment	R
Common ATE	3
Bulk items	Q
Training material not currently in the DOD inventory	S
Training material currently in the DOD inventory	T
End item	W
Spare (repairable support item)	X
Repair part (a nonrepairable consumable support item, component, assembly)	Y
Repair parts kit	Z
A repair part, component or assembly contained in a kit/set.	9
Tool kit/set	V
Program (embedded software)	E
Technical manuals	F
Forms or records	J
Electrostatic discharge sensitive item	K
Electromagnetic sensitive item	L
Facilities	U
System peculiar spare part	AA
Maintenance significant consumable	AB
Modified hand tool	AC
Maintenance assist module	AD
Attaching hardware	AE
Training Equipment	AF

0470 ITEM DESIGNATOR CODE 26 X - -

A part of nomenclature which provides a method for identifying equipment, usually by broad performance and use characteristics and general configuration. It is a data chain consisting of all or part of the data products type, model, and series designators, in that order.

Instructions for coding the type, model, and series designators are contained in MIL-STD-1812 and consists of the following subfields:

a. Type designator 7 X L -

A broad categorization of equipment based upon function or use.

b. Model designator 10 X L -

Identifies equipment within a particular type designator having essentially the same performance characteristics.

c. Series designator 2 X L -

Identifies equipment within a particular model designator having the same basic design, but not necessarily the same configuration.

MIL-PRF-49506
APPENDIX B

d. Suffix designator 7 X L -

Supplemental information used with type, model, series designators for items can be found in MIL-STD-196.

ITEM DESIGNATOR - END ARTICLE. The item designator code of the end article used in the Support Equipment Recommendation Data (SERD) Report.

ITEM DESIGNATOR - GOVERNMENT. The government-type designator.

0480 ITEM NAME 40 X L -

An identifying noun with appropriate adjective modifier, as contained in Federal Item Name Directory for Supply Cataloging, H6-1. Item Names contained in Federal Item Name Directory for Supply Cataloging, H6-1, cannot be abbreviated unless approved by the requiring authority.

ITEM NAME - ARTICLE REQUIRING SUPPORT. Item name for the article requiring support.

ITEM NAME - SE. The name of the piece of support equipment.

0490 ITEM NAME CODE 5 N F -

A number which serves as a cross-reference to each approved item name as contained in the Federal Item Name Directory for Supply Cataloging, H6-1. Names and noun concepts other than approved item names or noun concepts are assigned Item Name Code "77777".

0500 ITEM NUMBER 4 X R -

An index number assigned to an item for a specific illustration.

0510 JULIAN DATE - SPI NUMBER 7 N F -

The Julian date consists of the last two numbers of the calendar year and the numeric day of the year, i.e., February 5, 1990, would be 1990036.

0520 LINE REPLACEABLE UNIT (LRU) 1 A F -

An LRU is an essential support item which is removed and replaced at field level to restore the end item to an operationally ready condition. Conversely, a non-LRU is a part, component, or assembly used in the repair of an LRU, when the LRU has failed and has been removed from the end item for repair.

Item is an LRU	Y
Item is not an LRU	N

0530 LOT QUANTITY 12 N - -

A two-part sequence identifying the purchase/production lot quantity ranges to which the Unit of Measure (UM) or Unit of Issue (UI) price apply. The field is divided into two subfields for beginning and ending lot size. The Lot Quantity From must be less than or equal to the Lot Quantity To.

a. From 6 N R -

The beginning Lot Quantity of the item to which the UM/UI PRICE applies.

b. To 6 N R -

MIL-PRF-49506
APPENDIX B

The ending Lot Quantity of the item to which the UM/UI PRICE applies.

0540 MAINTENANCE ACTION CODE (MAC) 1 A F -

A code which indicates the required action to be taken at the expiration of the Maximum Allowable Operating Time (MAOT).

Calibrate	B
Condemn	C
Scheduled maintenance (as specified in the technical manual of planned maintenance system (PMS) and not covered by another MAC)	S
Repair	R
Test and Repair	T

0550 MAINTENANCE REPLACEMENT FACTOR (MRF) 18 N - -

a. Depot Level Repairables 6 N R 3

The expected rate at which an item is beyond the capability of maintenance (BCM) below the depot level and is inducted at the depot for repairs or condemnation per maintenance cycle.

b. Field Level Repairables 6 N R 3

The predicted number of times an item will require replacement (due to failure, forced removal) and be disposed of at the Organizational/Intermediate levels of maintenance in one maintenance cycle.

c. Consumables 6 N R 3

The predicted number of times an item will require replacement (due to failure, forced removal) and be disposed of at the Organizational/Intermediate levels of maintenance in one maintenance cycle. The calculations for MRF may be computed as follows:

- a. MRF Depot Level Repairables
MRF=[MTD(D)+MTD(CAD)] X MRRI
- b. MRF Field Level Repairables
MRF=[MTD(*)+MTD(CBD)] X MRRI
* = O, F or H as applicable

c. MRF Consumables
MRF=MRRI

Legend:

MTD = Maintenance Task Distribution (DPD# 0580)
MRRI = Maintenance Replacement Rate I (DPD# 0560)

0560 MAINTENANCE REPLACEMENT RATE I (MRRI) 8 N R 4

The MRRI is defined as the peacetime replacement rate factor for the item indicating the number of expected failures, which will require removal and replacement of the support item below depot level in a given next higher assembly per equipment/end item per year. This factor is to be based on the known/estimated end item usage and mature failure rates.

The MRRI can be calculated using the following:

For an assembly:

MIL-PRF-49506

APPENDIX B

$$\text{MRR (assembly)} = \sum_{i=1}^N \text{TF}_i \times \text{Quantity per task}_i$$

Where:

N = Number of remove and replace function tasks for a given IPC/AIPC combination (except D O/M levels)

TF_i = Task frequency (annual number of occurrences)

For a repair part:

$$\text{MRR (repair part)} = \sum_{i=1}^N \text{TF}_i \times \text{Quantity per task}_i$$

Where:

N = Number of repair function tasks performed against the next higher assembly of the repair part

TF_i = Task frequency (annual number of occurrences)

0570 MAINTENANCE REPLACEMENT RATE II 8 N R 3
(MRRII)

The MRRII can be defined by each of the following options:

Option 1. The MRRII is the replacement rate of the item calculated as follows:

$$\text{MRRII} = \text{MRR I} \times \frac{\text{annual operating program wartime}}{\text{annual operating program peacetime}}$$

When this computation results in zero, use the following definition:

The MRRII is the replacement rate of the line item per wartime operating program. The wartime operating program will be provided by the requiring authority. The MRRII will consider secondary failures, idleness, operator error, preventive/planned maintenance, handling, and storage.

Option 2. The MRRII is the wartime replacement rate for the item indicating the number of expected failures, which will require removal and replacement of the support item below depot level in a given next higher assembly per equipment/end item per year. This factor is to be based on the known/estimated end item usage and will include consideration of intensified rate of usage; increased stress due to combat operations; accident rate; ballistic damages; and differences in turnaround time.

0580 MAINTENANCE TASK DISTRIBUTION 14 N - -

The percentage of a repairable item expected to be repaired and returned to stock by a specified maintenance level. The field is divided into subfields by maintenance level. The sum of all subfields will always total 100 percent. The sum of MTD subfields up to each O/M level must be less than or equal to the sum of the Replacement Task Distribution (RTD) up to the corresponding O/M level.

a. Maintenance Task Distribution at 2 N R
Organizational/On Equipment/Unit-Organizational (O)

b. Maintenance Task Distribution at 2 N R -
Intermediate/Direct Support/Afloat/Third Echelon/Off Equipment/
Intermediate-Forward (F)

MIL-PRF-49506
APPENDIX B

c. Maintenance Task Distribution at Intermediate/General Support/Ashore/Fourth Echelon/Intermediate-Rear (H) 2 N R -

d. Maintenance Task Distribution at Specialized Repair Activity (L) 2 N R -

e. Maintenance Task Distribution at Depot/Shipyards (D) 2 N R -

f. Maintenance/Task Distribution at Condemnation Below Depot (CBD) 2 N R -

g. Maintenance Task Distribution at Condemnation At Depot (CAD) 2 N R -

0590 MATERIAL 240 X L -

A narrative description identifying the chemical compound or mechanical mixture properties of which the item is fabricated.

0600 MATERIAL LEADTIME 3 N R -

The order and ship time, in weeks, for critical/strategic materials used in manufacture of the item.

0610 MATERIAL WEIGHT 6 N R 3

The amount, in pounds, of critical/strategic material contained in an item. This data is required for items assigned an IMAC code.

0620 MAXIMUM ALLOWABLE OPERATING TIME (MAOT) 4 X - -

The expressed period of time after which certain items will be maintained in accordance with the Maintenance Action Code. The MAOT is composed of the following:

a. First two-positions. Number of applicable program units; i.e., 01-99.

b. Third-position. Appropriate multiplier code.

1 X program units	Blank
10 X program units	X
100 X program units	C
1000 X program units	M

c. Fourth-Position. Code to designate the program units.

Arrestments	A
Launches	C
Hours	H
Miles	M
Rounds	R
Starts	S
Landings	L
Days	D
Months (for provisioning purposes only)	T
Steaming/underway hours	U
Years	Y

0630 MEAN TIME BETWEEN FAILURES (MTBF) 10 D - -

For a particular interval, the total functional life of a population of an item divided by the total number of failures within the population during the measurement interval. The definition holds for time, rounds, miles, events, or other measure of life units.

MTBF - SE. An MTBF of that piece of SE.

0640 MEAN TIME TO REPAIR (MTTR) 5 N R 2

The total elapsed time (clock hours) for corrective maintenance divided by the total number of corrective maintenance actions during a given period of time. The MTTR may be calculated by the following:

$$MTTR = \frac{\sum_{I=1}^N (TF_i) \times (ET_i)}{\sum_{I=1}^N TF_i}$$

Where:

- I = On equipment corrective maintenance actions
- TF_i = Task frequency (annual number of occurrences of "I" on equipment maintenance action)
- N = Total number of on equipment corrective maintenance actions charged against the IPC/AIPC item under analysis
- ET_i = Mean elapsed time of the "I" on equipment corrective maintenance action

MTTR - SE. The MTTR of that piece of SE.

0650 MEASUREMENT BASE (MB) 1 A F -

A single position code which identifies the measurement unit for a particular operating time period or number of events.

Message units	A
Cycles	C
Days	D
Flight hours	F
Minutes	G
Hours	H
Kilometers	K
Landings	L
Miles	M
Operating hours	O
Rounds	R
Starts	S
Months	T
Underway/steaming hours	U
Years	Y
Arrestments	E
Catapults	B

MEASUREMENT BASE - MEAN TIME BETWEEN FAILURE. An MB for the mean time between failure.

MEASUREMENT BASE - WEAROUT LIFE. An MB for the wearout life.

MEASUREMENT BASE - MTBF SE. An MB for the MTBF for a piece of SE.

0660 METHOD OF PRESERVATION 2 X F -

MIL-PRF-49506

APPENDIX B

A code which defines the preventive measures to forestall deterioration resulting from exposure to atmospheric conditions during storage and shipment. For applicable codes, see MIL-STD-2073.

0670 MOBILE FACILITY CODE 1 A F -

A code which expresses the applicability of the SE to mobile facilities. The following codes may be used:

SE required for mobile facility only	V
SE not suitable for mobile facilities	X
Support not restricted to mobile facilities or other site categories	N

0680 NATIONAL STOCK NUMBER AND RELATED DATA 20 X - -

A number assigned under the Federal Cataloging Program/North Atlantic Treaty Organization (NATO) codification of equipment system to each approved item identification which provides a unique identification of an item of supply within a specified Federal Supply Classification (FSC). The field consists of a three-character prefix, a 13-character National Stock Number (NSN), and a four-character suffix code as follows:

a. Prefix

Cognizance code	2 X F -
Materiel control code	1 X F -

b. NSN

Consists of the following subfields:

Federal supply classification (FSC)	4 N F -
National item identification number (NIIN)	9 X F -

NOTE: An alphanumeric NIIN is used to document management control or temporarily assigned numbers prior to final NSN assignment. Final NSNs are completely numeric.

NSN - CONTAINER. A number which provides a unique identification to a reusable (long file) container within the appropriate FSC.

c. Suffix

Special materiel identification code/ Materiel management aggregation code	2 X F -
Activity code	2 X F -

For applicable codes, see DOD 4100.39-M.

0690 NEXT HIGHER ASSEMBLY PROVISIONING LIST ITEM SEQUENCE NUMBER (NHA PLISN) 5 X L -

The PLISN assigned to the item's next higher assembly. This may be the PLISN assigned to the item's kit, or the PLISN assigned to a major component which is a planned overhaul candidate for which the item is required.

0700 NEXT HIGHER ASSEMBLY PROVISIONING LIST ITEM SEQUENCE NUMBER INDICATOR (NHA IND) 1 X F -

MIL-PRF-49506
APPENDIX B

A field divided into nine subfields which describes technical capabilities/characteristics that an item of operational equipment, TMDE, or calibration equipment/standard is capable of measuring/generating, or which are to be measured on the UUT. Classified parameters and transistor logic levels are not listed in the CMRS. Classified parameters are listed in a classified supplement or appendix to the CMRS and that document appropriately controlled.

a. Input/Output (I/O) 1 A F -

A code specifying the corresponding parameter of the equipment in question (SE or UUT) as an input into equipment or output from the equipment. Codes are as follows:

Input into equipment	I
Output from equipment	O

INPUT/OUTPUT CODE - CATEGORY III SE. An I/O code of the SE UUT.

INPUT/OUTPUT CODE - SUPPORT EQUIPMENT. An I/O code of the SE.

INPUT/OUTPUT CODE - UUT. An I/O code of the UUT.

b. Parameter 20 X L -

The characteristic (e.g., volts, DC, Hertz, etc.) which an SE item is capable of measuring, or which are to be measured on the UUT.

PARAMETER - CATEGORY III SE. The parameter that the Category III SE item can measure.

PARAMETER - SUPPORT EQUIPMENT. The parameters of the SE.

PARAMETER - UUT. The parameters of the UUT that need to be measured.

c. Range-From 10 D - -

The lowest value of a particular parameter which can be measured or generated.

RANGE FROM - CATEGORY III SE. The lowest value of the parameter of the SE UUT that the SE under analysis must measure.

RANGE FROM - SUPPORT EQUIPMENT. The lowest value of the parameter that the SE is capable of measuring.

RANGE FROM - UUT. The lowest value of the parameter of the UUT that the SE under analysis must measure.

d. Range-To 10 D - -

The highest value of a particular parameter which can be measured or generated.

RANGE TO - CATEGORY III SE. The highest value of the parameter of the SE UUT that the SE under analysis must measure.

RANGE TO - SUPPORT EQUIPMENT. The highest value of the parameter that the SE is capable of measuring.

RANGE TO - UUT. The highest value of the parameter of the UUT that the support equipment under analysis must measure.

MIL-PRF-49506
APPENDIX B

e. Accuracy 26 X L -

A narrative description of the tolerances of the corresponding parameter.

ACCURACY - CATEGORY III SE. The amount of accuracy of the parameter of the SE UUT that the SE under analysis must measure.

ACCURACY - SUPPORT EQUIPMENT. The amount of accuracy of the parameter that the SE is capable of measuring.

ACCURACY - UUT. The amount of accuracy of the parameter of the UUT that the support equipment under analysis must measure.

f. Range/Value Code (R/V) 1 A F -

A code used to identify specific parameters as either a "range" or a specific "value". List specific value parameters in the "Range-From" block.

Range	R
Value	V

RANGE/VALUE CODE - TEST DEVICE. The R/V of the SE UUT.

RANGE/VALUE CODE - SUPPORT EQUIPMENT. The R/V of the SE.

RANGE/VALUE CODE - UUT. The R/V of the UUT.

g. Operational/Specification Parameter 1 A F -

A code indicating whether the associated parameter is operational or specification parameter of the UUT.

Operational parameter	O
Specification parameter	S

0780 PASS THROUGH PRICE 8 N R -

The cost added to items bought by a prime contractor which are delivered to the government with little or no value added by the prime contractor.

0790 PRECIOUS METAL INDICATOR CODE (PMIC) 1 X F -

A code which indicates the amount and type of precious metal contained in a specific reference numbered item. For applicable codes, see DOD 4100.39-M.

0800 PREPARING ACTIVITY 25 X L -

The name of the activity preparing SE data.

0810 PRESERVATION MATERIAL CODE 2 X F -

A code which indicates the material used to prevent or inhibit corrosion or deterioration of an item. For applicable codes, see MIL-STD-2073.

0820 PRIOR ITEM PROVISIONING LIST ITEM SEQUENCE NUMBER (PRIOR ITEM PLISN) 5 X L -

The PLISN which appeared on the Interim Support Items List, the Long

MIL-PRF-49506
APPENDIX B

Lead Times Items List, or first appearance of item in incremental provisioning submittals.

0830 PRODUCTION LEAD TIME (PLT) 2 N R -

The computed or expected time interval (in months) between placement of a new contract and shipment of the first deliverable quantity.

0840 PROGRAM PARTS SELECTION LIST (PPSL) 1 A F -

A code indicating whether the part is included within contractually controlled Federal Supply Classes (FSC), as outlined in MIL-STD-965, Parts Control Program. Codes assigned are as follows:

Part is included in contractually controlled FSCs and approved for use in PPSL A

Part is included in contractually controlled FSCs and not approved for use in PPSL N

0850 PRORATED EXHIBIT LINE ITEM NUMBER (PRORATED ELIN) 6 X - -

The ELIN which was assigned to the previous item procurement on an item affected by proration. When authorized by the government, the contractor may utilize an ELINs previously assigned by the government when submitting Design Change Notices (DCN). If the proration is a result of a design change, enter the new Prorated "TO ELIN" as specified by the requiring authority.

0860 PRORATED ELIN QUANTITY 6 N R -

The specific quantity remaining on order for the Prorated ELIN.

0870 PROVISIONING CONTRACT CONTROL NUMBER (PCCN) 6 X F -

A number assigned by the requiring authority to identify a specific contract or a group of end items/components that can have many configurations/models.

NOTE: The first position shall be alphabetic and will identify the applicable military service/agency provisioning designator having responsibility for the item(s) being processed.

First position codes are as follows:

Army	A-I
National Security Agency	J
Federal Aviation Administration (FAA)	K
Marine Corps	L&M
Navy	N-R
Air Force	S-X
Coast Guard	Y
Defense Logistics Agency	Z

0880 PROVISIONING LIST CATEGORY CODE (PLCC) 1 A F -

Codes which indicate whether the item is documented on another list or is a government furnished item.

Government furnished	A
Interim support items	B
Long lead time item	C

APPENDIX B

activity. The QPA for an "A" indented item must always be 1.

Option 1. The contractor shall enter the total number of times the line item is used in the assembly of which it is a part. Note: Option 1 QPEI can only be used with Option 1 QPA.

Option 2. For PPLs in reference designation format, enter the number of times the item appears at the location in the end item documented by the PPL. When an assembly is broken down by individual piece parts at its first appearance, the quantity for the assembly and for each piece part at each location shall be the number of times it appears in the assembly multiplied by the number of appearances of the assembly in the end item. For other provisioning lists under option 2, the QPA can be considered as the Quantity Per End Item (QPEI).

Option 3. The contractor shall enter the total number of times the line item is used in the assembly of which it is a part. An assembly only needs to be broken out to its piece parts at its first occurrence on a list. Subsequent appearances of the same assembly shall not be broken out.

0940 QUANTITY PER ASSEMBLY/QUANTITY PER END ITEM INDICATOR 1 N F -

A code signifying the option of QPA and QPEI

Option 1	1
Option 2	2
Option 3	3
Other	4

0950 QUANTITY PER END ITEM 5 A L -
(QPEI) 5 N R -

The total number of times the line item is used in the complete system/equipment. If the quantity is unknown or cannot be determined, specify the quantity by "V" (variable) or as specified by the provisioning activity. When numeric, the QPEI must be greater than or equal to the QPA. Exception, if the item does not have an NHA, the QPEI should be blank. The QPEI for an "A" indented item must always be 1.

Note: The Greek "Σ" or SIGMA represents the mathematical symbol for a series summation while the symbol "Π" or TAU is the mathematical expression for a series multiplication.

Option 1. The quantity per equipment or end item shall be entered only on the first appearance of the line item on the list. Subsequent appearances of the same item should be indicated by printing the letters "REF" in positions 1-3 to indicate that the total number of uses of the item in the equipment or end item has previously been listed. Note: This option can only be used with option 1, QPA.

The following applies to option 1:

$$QPEI = \sum_{I=1}^N [\prod_{j=1}^M QPA_j]_I$$

Where:

- N = Number of applications for unique part
- I = Application of unique part
- M = Number of indenture levels
- j = Indenture level of application

MIL-PRF-49506
APPENDIX B

Option 2. The QPEI shall be entered only on the first appearance of the item on the list. Subsequent appearances of the same assembly or subassembly should be indicated by printing "REFX" in positions 1-4. Subsequent appearances of the same repair part (i.e., a part which has no lower indentured parts) should be indicated by printing the letters "REF" in positions 1-3. This option can only be used with option 2, QPA.

Examples of provisioning lists with a single assembly breakdown using the option 2 QPA follow: Note that a separate application (PLISN and IPC) is required for each identical item in the same NHA.

1. For Reference Designation (RD) oriented equipment.

<u>RD</u>	<u>Reference No.</u>	<u>QPA</u>	<u>QPEI</u>
1A1	ABC	0003	0003
1A1 R1	PDQ	0003	0006
1A1 R2	PDQ	0003	REF
1A1 MP2	XYZ	0006	0006
1A2	ABC	0000	REFX
1A3	ABC	0000	REFX

2. For nonreference designation oriented equipment:

<u>Indenture Code</u>	<u>Reference No.</u>	<u>QPA</u>	<u>QPEI</u>
B	ABC	0001	0003
C	PDQ	0003	0006
C	PDQ	0003	REF
C	XYZ	0006	0006
B	ABC	0001	REFX
B	ABC	0001	REFX

The following applies to option 2:

$$QPEI = \sum_{I=1}^N QPA_i$$

Where:

- N = Number of applications for unique part
- I = Application of unique part

Option 3. The QPEI shall be entered only on the first appearance of the line item on the list for system/equipment for which the list is prepared, and should equal the total number of appearances of the item in that system/equipment (all appearances of an item may not appear on the list). Subsequent appearances of the same assembly or subassembly should be indicated by printing "REFX" in positions 1-4. Subsequent appearances of the same repair part (i.e., a part which has no lower indentured parts) should be indicated by printing the letters "REF" in positions 1-3. This option can only be used with option 3 of the QPA.

The following applies to option 3:

$$QPEI = \sum_{I=1}^N \left[\prod_{j=1}^M QPA_j \right]_I + \sum_{k=1}^{P-1} \left[\prod_{l=1}^Q QPA_l \right]_k$$

Where:

- N = Number of applications of unique part (first appearance of NHA

MIL-PRF-49506

APPENDIX B

only)

- I = Application of unique part
- M = Number of indenture levels
- j = Indenture level of application at first appearance
- P = Number of applications of unique assembly containing unique part
- k = Application of unique part (other than first appearance of a higher assembly)
- Q = Number of indenture levels at assembly application (other than first appearance of a higher assembly)
- l = Indenture level of application (other than first appearance of a higher assembly)

Note: The first product and summation in this formula are performed against the first appearance of an item. These applications are documented in the hardware breakdown. The second product and summation are performed against subsequent appearances of an item which are not documented. These item applications are identified by the first appearance of the item in an assembly (either NHA or higher) and the reference number of the higher assembly containing the unique part appearing in multiple applications.

0960 QUANTITY PER FIGURE 3 N R -

The total quantity of an item which is depicted by a specific illustration. Quantity per figure is left blank, if the quantity per assembly equals the quantity per figure.

0970 QUANTITY PER TEST 3 N R -

The number of end article system(s)/subsystem(s) or components required to enable the SE end item to perform properly (e.g., other components/subsystems may be required to be intact in order to use the SE).

0980 QUANTITY PER UNIT PACK 3 N R -
3 A F -

The number of units of an item packaged as a unit pack (see MIL-STD-2073 for codes and explanations).

0990 QUANTITY PROCURED 6 N R -

The total quantity of the provisioned item order.

1000 QUANTITY SHIPPED 6 N R -

The quantity of items affected by the design change notice that have been shipped.

1010 RECOMMENDED MINIMUM SYSTEM STOCK LEVEL 3 N R -

A numeric value representing the recommended minimum level of system stock required to support initial deployment of a system/equipment.

1020 RECURRING COST 8 N R -

The cost which is subsequent to technical data package availability and does not include developmental costs.

1030 REFERENCE DESIGNATION 64 X L -

Letters or numbers, or both, used to uniquely identify and locate

MIL-PRF-49506
APPENDIX B

discrete units, portions thereof, and basic parts of a specific component. The reference designation should result in the arrangement of provisioning lists for electronic and electronic related equipment being in alphanumeric reference designation order IAW IEEE 200-75, or in top-down or disassembly order as directed by the requiring authority. Parts for which reference designations have not been assigned, and for which disassembly sequencing is not possible, shall be listed in alpha-numeric part number or related data sequence. (Note: Compression (gang listing) of reference designations under one PLISN: Identical items identified by separate reference designators shall not be combined under a single PLISN unless authorized by the requiring authority.) For commercially designed, controlled, and commercially available electronic equipment, compliance with IEEE 200-75 is desired, but not mandatory. For reference designation oriented equipment, the reference designation shall be developed IAW IEEE 200-75, utilizing option 1 or 2 as prescribed by the requiring authority.

Option 1. Unit Numbering Method. When the unit numbering method is used, unit and subassembly portion (prefix) of the reference designation shall consist of up to 19 positions. The first 19 positions relate to assemblies and subassemblies.

Option 2. Block Numbering Method. When the block numbering method is used, the Joint Electronics Type Designation System (JETDS) nomenclature (type designation) for the unit shall be entered IAW the block numbering method. For nonelectronic items appearing in electronic equipment, use the identifying number or other symbol used to identify the item (e.g., figure and item number, up to 29 positions).

For nonreference designation oriented equipment, the requiring authority may request one of the following options be used:

Option 3. The volume, figure, and item number from the equipment technical manual will be used in lieu of the reference designation.

Option 4. The plan and piece number (drawing and piece identification) shall be used in lieu of the reference designation.

Option 5. The first precedence reference number.

1040 REFERENCE DESIGNATION CODE (RDC) 1 A F -

A code which indicates the type of data entered in reference designation block.

Assemblies that are separable or reparable identified with a reference designation IAW IEEE 200-75 (does not apply to detail parts within the assembly). A

Same as A, except this code is to be assigned to assemblies that are inseparable or nonreparable. U

Items identified with a volume, figure, and index number in the reference designation block. F

Installation and checkout items that are inseparable or nonreparable. C

Installation and checkout items that are separable or reparable. Z

MIL-PRF-49506
APPENDIX B

Equipment assemblies/subassemblies identified by drawing or assembly part numbers, with parts identified by circuit reference designator, number, part number or ship's plan and piece number.	H
Repairable accessories, tools, test, and SE identified as specified for Code "H".	T
Repairable accessories, nonrepairable assemblies, and material, including common and bulk items, not required to be identified with reference designation.	R
Nonrepairable accessories, tools, test and SE not included in code "T" breakdown.	S

1050 REFERENCE NUMBER

32 X L -

Any number, other than a government activity stock number, used to identify an item of production, or used by itself or in conjunction with other reference numbers to identify an item of supply. Reference numbers include part or identifying number, drawing, model, type, item designator or source controlling numbers; manufacturer's trade name; specification or standard numbers; and specification or standard part, drawing, or type numbers (for applicable formats see DOD 4100.39-M). The following precedence for reference number assignment should be used:

a. First Precedent Reference Number. The line item is identified by a government or industry association's specifications, drawing, or standard number, e.g., FED, MIL, JAN, AN, NEMA, SAE, which completely identifies the item including its physical, mechanical, electrical, and dimensional characteristics. (If the government or industry association's specification or standard number does not fully identify the item, then the actual manufacturer's identifying reference number becomes the first precedent reference number.) If the government or industry specification, drawing, or standard completely identifies the item, at least one additional reference number citing a manufacturer or vendor reference number must be provided.

b. Second Precedent Reference Number. When the line item is identified as, "source control," "altered," or "selected" (MIL-T-31000), the contractors assigned number is used.

c. Third Precedent Reference Number. The item identifying part, drawing, or catalog number of the actual manufacturer who supplies the item. The manufacturer is the company or government activity exercising design control over the item.

REFERENCE NUMBER - AID. A reference number of the adapter/interconnector device used in conjunction with the SE.

REFERENCE NUMBER - ARN ITEM. A reference number of the primary item under analysis.

REFERENCE NUMBER - ARTICLE REQUIRING SUPPORT. A reference number of the article requiring support.

REFERENCE NUMBER - AUTOMATIC TEST EQUIPMENT. A reference number of the ATE.

MIL-PRF-49506
APPENDIX B

REFERENCE NUMBER - CATEGORY III SE. A reference number of the SE that is measuring the SE UUT.

REFERENCE NUMBER - SUPPORT EQUIPMENT. A reference number of the SE under analysis.

REFERENCE NUMBER - TEST PROGRAM SETS. A reference number of the test program sets being used in conjunction with the SE.

REFERENCE NUMBER - UUT. The reference number of the UUT which is identical to the piece of SE.

REFERENCE NUMBER (ARN) - ADDITIONAL. A drawing or interchangeable reference number related to the reference number of the item under analysis. Only those ARNs that are known and available as a result of the contractor's design and production experience should be provided. This requirement is not intended to burden the contractor with the additional work load of searching for ARNs. When more than one manufacturer's reference number identifies a single design item, the additional reference number(s) which have been validated by the contractor as completely interchangeable for the specific application and whose use will not invalidate the end item warranty shall be furnished.

1060 REFERENCE NUMBER CATEGORY CODE (RNCC) 1 X F -

A code assigned to the reference number to indicate the category or relationship of the number to an NSN or another reference number (for applicable codes see DOD 4100.39-M).

RNCC - ARN. The code assigned to the additional reference number.

1070 REFERENCE NUMBER VARIATION CODE (RNVC) 1 N F -

A code assigned to a reference number to indicate that the cited number is item identifying, is not item identifying or is a reference number for information only (for applicable codes see DOD 4100.39-M).

RNVC - ARN. The code assigned to the additional reference number.

1080 REPAIR CYCLE TIME 18 N - -

The elapsed time, in days, of the complete repair cycle for a reparable item expected at each maintenance level. The subfield values must be either blank or greater for each higher O/M level. The O/M levels in ascending order are O/F/H/L/D and Contractor.

a. First Subfield 3 N R -

Repair Cycle Time at Organizational/On Equipment/Unit-Organizational level.

b. Second Subfield 3 N R -

Repair Cycle Time at Intermediate/Direct Support/Afloat/Third Echelon/Off Equipment/Intermediate-Forward level.

c. Third Subfield 3 N R -

Repair Cycle Time at Intermediate/General Support/Ashore/Fourth Echelon/Intermediate-Rear level.

MIL-PRF-49506
APPENDIX B

d. Fourth Subfield 3 N R -

Repair Cycle Time at Specialized Repair Activity (SRA).

e. Fifth Subfield 3 N R -

Repair Cycle Time at Depot/Shipyard.

f. Sixth Subfield 3 N R -

Contractor. An expressed period of time measured in days from receipt of a failed item at the contractor's facility until the item is returned to the designated receiving point (e.g., repair cycle time at contractor facility).

Option 1.

a. For O, F, H, and SRA, the elapsed time in days, beginning with the removal and replacement of an item to be repaired below depot level, and ending with the pickup of the serviceable item on the appropriate supply records.

b. For D, the number of days includes the time involved in the following:

(1) Removal and preparation of unserviceable items for shipment to CONUS air terminal or oversea aerial port.

(2) Shipment to air terminal/aerial port.

(3) Shipment from aerial port of embarkation to CONUS aerial port of disembarkation (oversea activities only). This entry should be weighted if the item is applicable to a variety of activities.

(4) Shipment from CONUS air terminal/aerial port to CONUS depot level maintenance activity.

(5) Receiving/shop planning/batching.

(6) Shop flow-time, including inspection.

(7) Packaging.

(8) Pickup on accountable records.

c. For contractor repairable items, the elapsed time in days from time of receipt of the failed item at the contractor's facility, until the item is returned to the designated receiving point.

Option 2. The elapsed time in days from receipt of a failed item at the maintenance level, until the item is ready for issue as a serviceable item.

1090 REPLACED OR SUPERSEDING 5 X L -
PROVISIONING LIST ITEM SEQUENCE NUMBER

The PLISN which is replacing or is being replaced in relationship to another PLISN.

1100 REPLACED OR SUPERSEDING 1 A F -
PROVISIONING LIST ITEM SEQUENCE NUMBER

MIL-PRF-49506
APPENDIX B

INDICATOR (RS/IND)

A code to indicate type of data entered in the Replaced or Superseding PLISN.

Replaced PLISN	R
Superseding PLISN	blank

1110 REPLACEMENT TASK DISTRIBUTION 15 N - -

The estimated percentage of the removals and replacements of an item that will be accomplished at each specified maintenance level. The sum of all subfields will always total 100 percent.

a. First Subfield 3 N R -

Replacement Task Distribution at Organizational/On Equipment/Unit - Organizational level.

b. Second Subfield 3 N R -

Replacement Task Distribution at Intermediate/Direct Support/Afloat/Third Echelon/Off Equipment/Intermediate-Forward level.

c. Third Subfield 3 N R -

Replacement Task Distribution at Intermediate/General Support/Ashore/ Fourth Echelon/Intermediate-Rear level.

d. Fourth Subfield 3 N R -

Replacement Task Distribution at SRA.

e. Fifth Subfield 3 N R -

Replacement Task Distribution at Depot/Shipyard.

1120 REVISION 2 A R -

An alphabetic code of one or two positions identifying a revision, such as A, B, ..., ZZ.

REVISION - SERD. A revision of the SERD.

1130 REWORK REMOVAL RATE (RRR) 3 N R 2

The percentage of the total quantity of a repairable assembly installed in an end item which will require some depth of rework concurrently with that end item.

1140 ROTATABLE POOL FACTOR (RPF) 6 N R 3

The predicted number of times in one maintenance cycle that an item is removed from its next higher assembly at the Organizational/Intermediate levels of maintenance, repaired at the Intermediate level and returned to stock at that level. The calculation for RPF maybe computed as follows:

$$RPF = [MTD(F) + MTD(H)] \times MRRI$$

Legend:

MTD = Maintenance Task Distribution (DPD# 0580)

MIL-PRF-49506
APPENDIX B

MRRRI = Maintenance Replacement Rate I (DPD# 0560)

1150 SAME AS PROVISIONING LIST 5 X L -
ITEM SEQUENCE NUMBER (SAME AS PLISN)

The PLISN assigned to a reference number and CAGE combination at its first appearance in a provisioning list for a PCCN. This PLISN is entered on each subsequent appearance of the reference number and CAGE combination in the provisioning list.

1160 SCOPE 40 X L -

A brief description of recommended or required data in question or data item description number.

SCOPE - DDCC. A short narrative describing the design data category.

SCOPE - IRCC. A short narrative describing the ILS requirement.

1170 SERIAL NUMBER EFFECTIVITY 20 X - -

A two-part sequence identifying the range of serial numbers of a specific group of end items or basic systems to which the item applies. Consists of the following subfields:

a. From 10 X L -

The beginning serial number in the range of serial numbers defined by Serial Number Effectivity. Serial Number Effectivity From must be less than or equal to Serial Number Effectivity To.

b. To 10 X L -

The ending serial number in the range of serial numbers defined by Serial Number Effectivity.

1180 SERVICE DESIGNATOR CODE (SER) 1 A F -

A single-position code identifying the military service or nonmilitary major governmental agency having jurisdiction over, or executive management responsibility for, the acquisition.

Army	A
Air Force	F
Coast Guard	Y
FAA	T
National Security Agency	S
Navy	N
Marine Corps	M
All military	X
FAA/all military	J
Other	O

SERVICE DESIGNATOR CODE - SE. A service designator responsible for the SE under analysis.

SERVICE DESIGNATOR CODE - USING. Multiple service designators which are users of the SE under analysis.

1190 SHELF LIFE (SL) 1 X F -

MIL-PRF-49506

APPENDIX B

A code assigned to an item to indicate a storage or SL time period for an item possessing deteriorative or unstable characteristics (see DOD 4100.39-M for applicable codes).

1200 SHELF LIFE ACTION CODE (SLAC) 2 X F -

A two-position code assigned to a SL item to specify the type of inspection, test, or restorative action to be taken when the item has reached its storage SL, and to specify the extension of the SL time period after the test/restorative action has been completed.

Check/inspect/test IAW CO
inventory managers instructions.

Incorporate all mandatory changes. If found C -
satisfactory, extend the previously established shelf life by an appropriate time period. The first position will always be "C". The second position, shown by a dash (-), will be filled in with a shelf life code from DOD 4100.39-M. This code will be used to indicate the time period that the shelf life may be extended after incorporation of the changes.

Incorporate all mandatory changes, perform CT
minor adjustment required, clean and relubricate bearings, reassemble, test to post overhaul standards, and correct any observed discrepancies. Items which pass tests shall be returned to stock as RFI (Ready For Issue). Exterior package marking of such items shall indicate the latest check and test date and the original date of manufacture. Items which fail test shall be placed in "F" condition.

To be tested by the laboratory/activity L -
after the initial shelf life has expired and at specified time intervals thereafter. The first position will always be "L". The second position, shown by a dash(-), will be filled in with a shelf life code from DOD 4100.39-M. This code will be used to indicate the time period at which samples should be periodically submitted to the laboratory/activity for testing after the initial shelf life has expired. If item fails test, take disposal action.

Replace all deteriorated and nonmetallic RD
components subject to deterioration (disassemble and process to the level required to permit replacement of deteriorable items; test to post-overhaul standards and return to stock as RFI item with fully restored storage time limitations). Exterior package marking of such items shall indicate the latest date of overhaul.

This is assigned to fuel metering equipment, RJ
which has been tested by other than MIL-C-7024.

MIL-PRF-49506

APPENDIX B

<p>Provides for equipment that has been tested with fluids indicated by Specification MIL-C-7024 and has not subsequently been operated with other fluids. (Use for fuel metering equipment only.)</p>	<p>RN</p>
<p>Salvage</p>	<p>SA</p>
<p>Request cannibalization/salvage instructions from inventory manager.</p>	<p>SB</p>
<p>Identification of Safety Items. A safety item designated by the requiring authority that is subject to a 5 year age limitation when used for purposes involving safety of personnel. Material in this category that is over 5 years old will not be used for repair or modification of personnel, drag, or special parachutes, or others used directly involving personnel safety. Use advice code 2H unless material is being used for cargo parachutes, or other uses not involving personnel safety.</p>	<p>S9</p>
<p>Test, if OK, extend previously established shelf life by an appropriate time period and process IAW with code RD. The first position will always be "T". The second position, shown by a dash (-), will be filled in with a shelf life code from DOD 4100.39-M. This code will be used to indicate the time period that the shelf life may be extended after passing test and processing IAW code RD. NOTE: For flight clothing, the second position of the code will be used to indicate the time interval at which periodic testing should be performed. If OK, return to stock as an RFI item; if not OK, make necessary repairs to the extent economically feasible and return to stock as RFI item.</p>	<p>T-</p>
<p>Unsuitable for restoration to issuable status. At end of shelf life period, material will be disposed of IAW existing instructions.</p>	<p>UU</p>
<p>Test. If item passes a test, extend the previously established shelf life by an appropriate time period. The first position will always be "X". The second position, shown by a dash (-), will be filled in with a shelf life code from DOD 4100.39-M. This code will be used to indicate the time period that the shelf life may be extended. If item fails tests, dispose of it IAW existing instructions.</p>	<p>X-</p>
<p>Non-deteriorative. When the shelf life is coded 0, then the shelf life action code of 00 is mandatory.</p>	<p>00</p>
<p>1210 SKILL SPECIALTY CODE FOR SUPPORT EQUIPMENT OPERATOR</p>	<p>7 X L</p>
<p>Describes the maintenance or operator skill required to operate the SE under analysis. See the requiring authority for a list of possible codes.</p>	

MIL-PRF-49506
APPENDIX B

1220 SOURCE, MAINTENANCE AND RECOVERABILITY (SMR) CODE 6 X L -

SMR codes are a series of alpha or alphanumeric symbols used at the time of provisioning to indicate the source of supply of an item, its maintenance implications, and recoverability characteristics. Applicable codes are specified in the joint regulation AR 700-82, OPNAVINST 4410.2, AFR 66-45, MCO 4400.120, DSAR 4100.6 publication.

1230 SPARES ACQUISITION INTEGRATED WITH PRODUCTION (SAIP) 1 A F -

An alphabetic code indicating that the item is a candidate for an SAIP list.

Item is an SAIP list candidate	Y
Item is not an SAIP list candidate	blank

1240 SPECIAL MAINTENANCE ITEM CODE (SMIC) 1 A F -

Codes which indicates any special maintenance category applicable to the line item. Codes assigned are as follows:

Nonrepairable	A
---------------	---

Factory repairable	B
--------------------	---

Matched set	C
-------------	---

Select at test	D
----------------	---

MAMS (Maintenance Assistance Modules). An item authorized or recommended by the government/contractor for procurement and location with the end item as the sole means of fault isolation in the event of failure. Contractor recommendations shall be IAW the maintenance philosophy approved by the government. (e.g., modules employed in diagnostic circuitry used for "built-in" fault isolation.)	F
---	---

Remain in Place. A repairable item which, upon removal without an immediate replacement, would: a. Destroy structural integrity; b. Endanger operating or maintenance personnel; or c. If partially degraded, cause total degradation of an essential function of the end item.	G
---	---

Safety. An item which, upon failure, would jeopardize the direct safety of operating or maintenance personnel.	H
--	---

Flight critical. The single failure of which, during any operating condition could cause loss of the aircraft or one of its major components, loss of control, unintentional release of, or inability to release any armament store, failure of weapon installation components, or which may cause significant personnel injury, including during launch or recovery, flight, escape, survival, or rescue.	J
--	---

MIL-PRF-49506

APPENDIX B

1250 SPECIAL MARKING CODE 2 X F -

A code which identifies special markings which are required as an integral part of the total pack to protect the contained item during preservation, packing, storage, transit, and removal from the pack. For applicable codes, see MIL-STD-2073.

1260 SPECIAL MATERIAL CONTENT CODE (SMCC) 1 X F -

A code indicating that an item represents or contains peculiar material requiring special treatment, precautions, or management control of the item (see DOD 4100.39-M for applicable codes).

1270 SPECIAL PACKAGING INSTRUCTION NUMBER 10 X L -

A number which identifies a specific special packaging instruction prepared IAW MIL-STD-2073.

1280 SPECIAL PACKAGING INSTRUCTION (SPI) NUMBER REVISION 1 A F -

A code which identifies the SPI revision.

Codes A through Z

1290 SUPPLEMENTAL PACKAGING DATA 59 X L -

Concise remarks or statements which are pertinent to the packaging process and are required in addition to that specific data documentation.

1300 SUPPORT EQUIPMENT DIMENSIONS 12 N - AS

The dimensions of an item of support/test equipment. Consists of the following subfields:

- a. Length 4 N R 1
- b. Width 4 N R 1
- c. Height 4 N R 1

SE DIMENSIONS OPERATING. Dimensions of an item of support/test equipment or training material while it is in the operational configuration mode.

SE DIMENSIONS SHIPPING. The dimensions of an item of support/test equipment as it is configured for shipment.

SE DIMENSIONS STORAGE. Dimensions of an item of support/test equipment or training material while it is in the storage configuration mode.

1310 SUPPORT EQUIPMENT EXPLANATION - - - -

Narrative statements used to explain a condition not readily identified in a given data product within the support equipment area, or a particular product which requires additional comment. When the information is related to a specific data product, the explanation should be prefaced with a reference to that product.

1320 SUPPORT EQUIPMENT RECOMMENDATION 10 X L -

MIL-PRF-49506

APPENDIX B

DATA NUMBER (SERD NUMBER)

A code assigned to identify a piece of support equipment having a unique Reference Number and Commercial and Government Entity (CAGE) Code.

1330 SUPPORT EQUIPMENT RECOMMENDATION - - - -
DATA REVISION/SUPERSEDURE REMARKS

Identify the reason for supersedure or revision for the SE.

1340 SUPPORT EQUIPMENT WEIGHT 6 N R 1

The weight of an item of support/test equipment.

SE WEIGHT OPERATING. The operating weight of the item under analysis.

SE WEIGHT SHIPPING. The weight of an item of support/test equipment as configured for shipment.

SE WEIGHT STORAGE. The weight of an item of support/test equipment or training material while it is in the storage configuration mode.

1350 TECHNICAL MANUAL CHANGE NUMBER 2 N R -
(TM CHG)

A change number reflecting the current edition of a specific manual.

1360 TECHNICAL MANUAL INDENTURE CODE 1 N F -
(TM IND)

A code used to indent item names in the repair part description column in a manual to depict disassembly parts relationship within a figure of the text. Codes are: "1" through "5", which indents the item in the parts manual listing by the number specified.

1370 TECHNICAL MANUAL NUMBER 30 X L -

The technical manual, technical order, or manual controlling number assigned by the requiring authority.

1380 TEST ACCURACY RATIO (TAR) 1 X F -

A one-position code specifying a ratio. The TAR is determined by dividing the maximum permitted error of the unit to be measured or calibrated by the maximum known error of the measuring or generating device used to perform the measurement.

<u>TAR Greater Than or Equal To</u>	<u>Code</u>
1:1	1
2:1	2
3:1	3
4:1	4
5:1	5
6:1	6
7:1	7
8:1	8
9:1	9
10:1	0

TEST ACCURACY RATIO - CATEGORY III SE. The actual TAR of the TMDE in conjunction with the SE UUT.

MIL-PRF-49506
APPENDIX B

TEST ACCURACY RATIO - UUT PARAMETER. The actual TAR of the TMDE in conjunction with the UUT.

1390 TOTAL ITEM CHANGES (TIC) 2 N R -

The number of times the item is affected by the design change or the cumulative total number of design changes affecting the item.

Option 1. The total number of times the line item is affected by the design change.

Option 2. The cumulative total number of design changes affecting the PLISN.

1400 TOTAL QUANTITY RECOMMENDED 6 N R -

A recommended quantity of an item required to support a specific number of applications for a specific period of time. The applications may be to a weapon system, end item, component or combinations thereof, which are contained in the applicable contract.

1410 TYPE EQUIPMENT CODE 4 X L -

A government supplied code identifying an end item in the maintenance data collection subsystem (MDCS) by its application to the specific type/model/series of aircraft or equipment which it supports.

1420 TYPE OF CHANGE CODE (TOCC) 1 A F -

This block, which is blank on initial submissions of provisioning data, shall be used as a type of change code to indicate deletions, modifications, typographical errors, quantity changes (increase, decrease), and limited part applications as follows:

- | | |
|--|---|
| Indicates a deleted item | D |
| Deletion of a data product | G |
| Item is replaced during production and support of the old part may be required for prior production quantities | L |
| Indicates a modified item. Required to identify entries for those items changed as a result of either administrative or engineering requirements (not for initial entry of NSN) before or during production. | M |

Examples of changes follow:

- a. Prime contractor's reference number
- b. Commercial and Government Entity Code
- c. Manufacturer's reference number
- d. Item name
- e. Other data products as may be subsequently defined, wherein the hardware is not affected.

- | | |
|--|---|
| Used to make quantity field changes | Q |
| Used to make a typographical error correction (not automatically assigned) | T |

1430 TYPE OF PRICE CODE 1 A F -

MIL-PRF-49506
APPENDIX B

A code used to define the type of UM or UI Price.

Engineering estimate	A
Federal catalog price	B
Vendor catalog price	C
Negotiated price	D

1440 TYPE OF STORAGE CODE 1 A F -

Indicates the type of storage space and environmental conditions to be maintained during storage or shipment. (See NAVSUP PUB 437, appendix 17, page 91, for specific usage.)

General purpose, unheated	A
General purpose, heated	B
General purpose, controlled humidity (maximum 40% RH ashore; as dry as possible afloat)	C
Heavy duty, unheated (overhead crane area) - over 100 cf or 1000 lbs	D
Heavy duty, heated (overhead crane area)	E
Heavy duty, controlled humidity (overhead crane area)	F
Flammable	G
Freeze (below 32 F)	H
Chill (between 32 F and 50 F)	I
Shed	J
Open	K
Explosive storage (non-ordnance items, such as explosive bolts and rivets)	L
Acid storage	M
Inert compressed gas storage (Naval Ships Technical Manual, chapter 9230, sections 23 and 24, provide stowage requirements and safety precautions for compressed gases)	N
Special storage (requires specific authority and stowage instructions)	O
Separate storage (fire producers, not elsewhere classified; keep away from acid, combustible, organic, and readily oxidizable materials)	P
Warehouse/flammable storage (prohibited for shipment storage)	Q
Warehouse/general storage (no special requirements; prohibited for shipboard storage)	R
Warehouse/special storage (requires specific authority and storage instructions; prohibited for shipboard storage)	S
Warehouse/separate storage (fire producers; keep away from acid, combustible, organic, and readily oxidizable materials; prohibited for shipboard storage)	T
Flammable compressed gas storage (Naval Ships Technical Manual, chapter 9230, sections 23 and 24, provides stowage requirements and safety requirements for compressed gases)	U
Oxidizing compressed gas storage (Naval Ships Technical Manual, chapter 9230, sections 23 and 24, provides stowage requirements and safety requirements for compressed gases)	V
Poisonous compressed gas storage (Naval Ships Technical Manual, chapter 9230, sections 23 and 24, provides stowage requirements and safety requirements for compressed gases)	W
Radioactive material. Store in a designated radioactive material area in accordance with afloat supply procedures, NAVSUP PUB 485.	X

NOTE: When one of certain Special Material Content Codes is assigned, the entry of a corresponding Type of Storage Code is required in accordance with the following table:

MIL-PRF-49506
APPENDIX B

<u>Special Material Content Code</u>	<u>Type of Storage Code</u>
B	U, V, or W
C, E, I, J, M, S, T, U or Y	O
F, G, or Z	G
P	O or W
Q	L
R	X
W	V, W, or N
X	O or X
1450 UNIT CONTAINER CODE	2 X F -
A code to identify the container used to hold the quantity unit pack. For applicable code, see MIL-STD-2073.	
1460 UNIT CONTAINER LEVEL	1 A F -
A code which indicates the highest level of packing protection provided by the unit container.	
Unit container not acceptable for shipping.	O
Unit container acceptable and provides level "A" protection.	A
Unit container acceptable and provides level "B" protection.	B
Unit container acceptable and provides level "C" protection.	C
Unit container not required.	D
Unit container is acceptable and provides minimum protection with commercial packaging.	X
Unit container is acceptable and affords, or is limited to, special consideration (e.g., air only, inside storage only).	Z
1470 UNIT OF ISSUE (UI)	2 A F -
A code which indicates the UI quantity of an item. The UI quantity is the managing activity's established accounting unit upon which the smallest unit pack is based, accountable records are maintained, and requirements are computed. For applicable codes see DOD 4100.39-M.	
1480 UNIT OF ISSUE CONVERSION FACTOR (UI CONVERSION FACTOR)	5 N - -
A quantitative multiplier used to convert the UM to the UI. The data product is composed of two subfields:	
a. <u>First Digit</u> . Decimal Locator Code	1 N F -
A digit (0, 1, 2, 3, or 4) indicating the number of places that the decimal must be moved from the right most position of the second subfield to describe correct decimal placement in that field.	
b. <u>Digits 2 through 5</u> . Factor	4 N R AS

MIL-PRF-49506
APPENDIX B

The numerical value of the conversion factor.

1490 UNIT OF ISSUE/UNIT OF MEASURE CODE 1 A F -

A code that identifies the associated information as either UI or UM related.

Unit of Measure M
Unit of Issue I

1500 UNIT OF ISSUE/UNIT OF MEASURE PRICE 10 N R 2
(UI/UM PRICE)

The price for one UI of an item or the best estimated price per UM. The last two positions of the field represent cents, and the decimal is understood.

1510 UNIT OF MEASURE (UM) 2 A F -

The UM, as defined in DOD 4100.39-M. The UM is abbreviated: dz, ea, ft, gl, in, lb, oz, etc., for dozen, each, foot, gallon, inch, pound, ounce, etc., respectively.

UNIT OF MEASURE - SE OPERATING DIMENSIONS. A UM associated with the length, width, and height of the SE in operational mode.

UNIT OF MEASURE - SE OPERATING WEIGHT. A UM associated with the weight of the SE in operational mode.

UNIT OF MEASURE - SE STORAGE DIMENSIONS. A UM associated with the length, width, and height of the SE in the storage mode.

UNIT OF MEASURE - SE STORAGE WEIGHT. A UM associated with the weight of the SE in the storage mode.

UNIT OF MEASURE - SUPPORT EQUIPMENT SHIPPING DIMENSIONS. A UM associated with the length, width, and height of the SE in the shipping mode.

UNIT OF MEASURE - SUPPORT EQUIPMENT SHIPPING WEIGHT. A UM associated with the weight of the SE in the shipping mode.

1520 UNIT PACK CUBE 7 N R 3

The length times width times depth (or cubic dimensions) of the unit container expressed in feet.

1530 UNIT SIZE 12 N - -

The length, width, and height of the item, as configured for packaging, expressed in inches. Subfields are as follow:

a. Length 4 N R 1
b. Width 4 N R 1
c. Height/Depth 4 N R 1

UNIT SIZE - PACK. The length, width, and depth of the unit container or package expressed in inches. The unit pack size must be greater than or equal to unit size

MIL-PRF-49506
APPENDIX B

1540 UNIT UNDER TEST EXPLANATION 240 x L -

Narrative statements which further explain, justify, or substantiate any data entry concerning UUT related data.

1550 UNIT WEIGHT 5 X - -

The unpackaged weight of the item expressed in pounds. The field is structured as follows:

a. For weights up to 9,999.9 5 N R 1

b. For weights over 9,999.9 5 X - -

First subfield. 1 A F -

Multiplier code indicates that the number entered in the second subfield should be multiplied by 10, 100, or 1,000 in order to correctly represent the unit weight. Codes are as follow:

10 X weight	A
100 X weight	B
1000 X weight	C

Second subfield. 4 N R AS

Numerical values of the weight expressed in pounds.

UNIT WEIGHT - PACK. The gross weight of the unit pack expressed in pounds. Unit pack weight must be greater than or equal to unit weight.

1560 USABLE ON CODE (UOC) 4 X L -

A code that indicates the configuration of a system/equipment on which the item under analysis is used. The UOC represents only one configuration/model of equipment. It is a one, two, three, or four-character alphanumeric entry with guidance for UOC assignment provided by the requiring authority.

USABLE ON CODE - DESIGN CHANGE. The UOCs affected by the design change.

USABLE ON CODE - SUPPORT EQUIPMENT. The UOCs of the SE.

1570 WEAROUT LIFE 6 N R -

The operational interval of flight hours, calendar time, or other appropriate, independent variables, from initial installation until an item can no longer perform its intended mission, due to the depletion of some physical property or material. For a family of items, wearout occurs when the conditional probability of failure (hazard rate) increases with increases of the independent variable.

1580 WORK UNIT CODE 7 X L -

An alphanumeric code used to identify a particular system, subsystem, component/assembly, or part of the system/equipment. Codes will be as specified by the requiring authority.

WORK UNIT CODE - ARTICLES REQUIRING SUPPORT. A code used to identify the article requiring support.

1590 WRAPPING MATERIAL 2 X F -

MIL-PRF-49506
APPENDIX B

A code which indicates the type of wrapping material to be used on the item. For applicable codes, see MIL-STD-2073.

MIL-PRF-49506
APPENDIX B

DATA PRODUCT DELIVERABLE: _____

This worksheet is used to select data deemed necessary by the government.
Data should be used to feed down stream government process.

<u>SELECT</u>	<u>EXPLANATION</u>
X	Data product required on all items
A	As applicable
T	Registered Support Equipment Only
U	Non-Registered Support Equipment Only
R	Repairables only
P	All "P" source code items
N	New "P" source code items
Y	National Stock Number items
O	"Ref" items only
F	First appearance items only
C	COTS items
I	NDI items
D	Developmental items
L	LRU/WRA items
S	SRA/SRU items
M	Packaging, Common items
B	Packaging, Bulk items
E	Support Equipment

NOTE: Other codes may be assigned by the program office as identified below.
Program specific selections and explanations.

FIGURE 2 - WORKSHEET 2 - LMI DATA PRODUCTS

MIL-PRF-49506
APPENDIX B

DATE PRODUCT TITLE	SELECT	ADDITIONAL INFORMATION
ALLOWANCE ITEM CODE (AIC)		
ALLOWANCE ITEM QUANTITY		
ALTERNATE INDENTURED PRODUCT CODE (AIPC)		
ALTERNATE IPC - UUT		
AUTOMATIC DATA PROCESSING EQUIPMENT CODE		
BASIS OF ISSUE (BOI)		
QUANTITY AUTHORIZED (QTY-AUTH)		
END ITEM		
LEVEL		
CONTROL		
CALIBRATION AND MEASUREMENT REQUIREMENTS SUMMARY RECOMMENDED		
CALIBRATION INTERVAL		
CALIBRATION ITEM		
CALIBRATION PROCEDURE		
CALIBRATION REQUIRED		
CALIBRATION TIME		
CHANGE AUTHORITY NUMBER		
CLEANING AND DRYING PROCEDURE		
COMMERCIAL AND GOVERNMENT ENTITY (CAGE) CODE		
CAGE CODE - ADAPTER INTERCONNECTOR DEVICE		
CAGE CODE - ARN		
CAGE CODE - ARN ITEM		
CAGE CODE - ARTICLES REQUIRING SUPPORT		
CAGE CODE - ATE		
CAGE CODE - CATEGORY III SE		
CAGE CODE - CTIC		
CAGE CODE - PACKAGING DATA PREPARER		
CAGE CODE - SUPPORT EQUIPMENT		
CAGE CODE - TEST PROGRAM SET		
CAGE CODE - UUT		

FIGURE 2 - WORKSHEET 2 - LMI DATA PRODUCTS

**MIL-PRF-49506
APPENDIX B**

CONTRACTOR FURNISHED EQUIPMENT/ GOVERNMENT FURNISHED EQUIPMENT (CFE/GFE)		
CONTRACTOR RECOMMENDED		
CONTRACTOR RECOMMENDED - DDCC		
CONTRACTOR RECOMMENDED - IRCC		
CONTRACTOR TECHNICAL INFORMATION CODE (CTIC)		
CONTROLLED INVENTORY ITEM CODE		
CRITICALITY CODE		
CUSHIONING AND DUNNAGE MATERIAL CODE		
CUSHIONING THICKNESS		
DEGREE OF PROTECTION CODE		
DEMILITARIZATION CODE (DMIL)		
DESCRIPTION/FUNCTION AND CHARACTERISTICS OF SUPPORT EQUIPMENT		
DESIGN DATA CATEGORY CODE		
DESIGN DATA PRICE		
END ITEM ACRONYM CODE (EIAC)		
ESSENTIALITY CODE		
ESTIMATED PRICE		
ESTIMATED PRICE - DDCC		
ESTIMATED PRICE - IRCC		
FIGURE NUMBER		
FRAGILITY FACTOR		
FUNCTIONAL ANALYSIS		
FUNCTIONAL GROUP CODE		
HARDNESS CRITICAL ITEM (HCI)		
HARDWARE DEVELOPMENT PRICE		
HAZARDOUS CODE		
INDENTURE CODE		
ATTACHING PART/HARDWARE		
OPTION 1		
OPTION 2		
OPTION 3		

FIGURE 2 - WORKSHEET 2 - LMI DATA PRODUCTS

MIL-PRF-49506
APPENDIX B

OPTION 4		
OPTION 5		
INDENTURE FOR KITS		
OPTION 1		
OPTION 2		
OPTION 3		
INDENTURE CODE - IPC		
INDENTURED PRODUCT CODE (IPC)		
INDENTURED PRODUCT CODE (IPC) - UUT		
INPUT POWER SOURCE		
OPERATING RANGE - MINIMUM		
OPERATING RANGE - MAXIMUM		
ALTERNATING CURRENT/DIRECT CURRENT		
FREQUENCY RANGE - MINIMUM		
FREQUENCY RANGE - MAXIMUM		
PHASE		
WATTS		
PERCENT MAXIMUM RIPPLE		
INSTALLATION FACTORS OR OTHER FACILITIES		
INTEGRATED LOGISTIC SUPPORT PRICE		
INTEGRATED LOGISTIC SUPPORT REQUIREMENTS CATEGORY CODE		
INTERCHANGEABILITY CODE		
INTERMEDIATE CONTAINER CODE		
INTERMEDIATE CONTAINER QUANTITY		
ITEM CATEGORY CODE (ICC)		
ITEM DESIGNATOR CODE		
ITEM DESIGNATOR - END ARTICLE		
ITEM DESIGNATOR - GOVERNMENT		
ITEM NAME		
ITEM NAME - ARTICLE REQUIRING SUPPORT		
ITEM NAME - SE		
ITEM NAME CODE		

FIGURE 2 - WORKSHEET 2 - LMI DATA PRODUCTS

**MIL-PRF-49506
APPENDIX B**

ITEM NUMBER		
JULIAN DATE - SPI NUMBER		
LINE REPLACEABLE UNIT (LRU)		
LOT QUANTITY		
FROM		
TO		
MAINTENANCE ACTION CODE (MAC)		
MAINTENANCE REPLACEMENT FACTOR (MRF)		
MRF - DEPOT LEVEL REPAIRABLES		
MRF - FIELD LEVEL REPAIRABLES		
MRF - CONSUMABLES		
MAINTENANCE REPLACEMENT RATE I (MRFI)		
MAINTENANCE REPLACEMENT RATE II (MRFII)		
OPTION 1		
OPTION 2		
MAINTENANCE TASK DISTRIBUTION		
MATERIAL		
MATERIAL LEADTIME		
MATERIAL WEIGHT		
MAXIMUM ALLOWABLE OPERATING TIME (MAOT)		
MEAN TIME BETWEEN FAILURES (MTBF)		
MEAN TIME BETWEEN FAILURES (MTBF) - SUPPORT EQUIPMENT		
MEAN TIME TO REPAIR (MTTR)		
MEAN TIME TO REPAIR (MTTR) - SE		
MEASUREMENT BASE (MB)		
MEASUREMENT BASE - MEAN TIME BETWEEN FAILURES		
MEASUREMENT BASE - MEAN TIME BETWEEN FAILURES - SUPPORT EQUIPMENT		
MEASUREMENT BASE - WEAROUT LIFE		
METHOD OF PRESERVATION		
MOBILE FACILITY CODE		
NATIONAL STOCK NUMBER - CONTAINER		

FIGURE 2 - WORKSHEET 2 - LMI DATA PRODUCTS

**MIL-PRF-49506
APPENDIX B**

FEDERAL SUPPLY CLASSIFICATION		
NATIONAL ITEM IDENTIFICATION NUMBER		
NATIONAL STOCK NUMBER AND RELATED DATA		
COGNIZANCE CODE		
MATERIEL CONTROL CODE		
FEDERAL SUPPLY CLASSIFICATION		
NATIONAL ITEM IDENTIFICATION NUMBER		
SPECIAL MATERIEL IDENTIFICATION CODE/ MATERIEL MANAGEMENT AGGREGATION CODE		
ACTIVITY CODE		
NEXT HIGHER ASSEMBLY PROVISIONING LIST ITEM SEQUENCE NUMBER (NHA PLISN)		
NEXT HIGHER ASSEMBLY PROVISIONING LIST ITEM SEQUENCE NUMBER INDICATOR (NHA IND)		
NOT REPARABLE THIS STATION (NRTS)		
OPERATOR'S MANUAL		
OPTIONAL PROCEDURE INDICATOR		
OVERHAUL REPLACEMENT RATE (ORR)		
PACKAGING CATEGORY CODE		
PACKING CODE		
PARAMETERS		
INPUT/OUTPUT CODE - CATEGORY III SE		
PARAMETER - CATEGORY III SE		
RANGE FROM - CATEGORY III SE		
RANGE TO - CATEGORY III SE		
ACCURACY - CATEGORY III SE		
RANGE/VALUE CODE - CATEGORY III SE		
INPUT/OUTPUT CODE - SUPPORT EQUIPMENT		
PARAMETER - SUPPORT EQUIPMENT		
RANGE FROM - SUPPORT EQUIPMENT		
RANGE TO - SUPPORT EQUIPMENT		
ACCURACY - SUPPORT EQUIPMENT		
RANGE/VALUE CODE - SUPPORT EQUIPMENT		
INPUT/OUTPUT CODE - UUT		

FIGURE 2 - WORKSHEET 2 - LMI DATA PRODUCTS

MIL-PRF-49506
APPENDIX B

PARAMETER - UUT		
RANGE FROM - UUT		
RANGE TO - UUT		
ACCURACY - UUT		
RANGE/VALUE CODE - UUT		
OPERATIONAL/SPECIFICATION PARAMETER		
PASS THROUGH PRICE		
PRECIOUS METAL INDICATOR CODE (PMIC)		
PREPARING ACTIVITY		
PRESERVATION MATERIAL CODE		
PRIOR ITEM PROVISIONING LIST ITEM SEQUENCE NUMBER (PRIOR ITEM PLISN)		
PRODUCTION LEAD TIME (PLT)		
PROGRAM PARTS SELECTION LIST (PPSL)		
PRORATED EXHIBIT LINE ITEM NUMBER (PRORATED ELIN)		
PRORATED ELIN QUANTITY		
PROVISIONING CONTRACT CONTROL NUMBER (PCCN)		
PROVISIONING LIST CATEGORY CODE (PLCC)		
PROVISIONING LIST ITEM SEQUENCE NUMBER (PLISN)		
PROVISIONING NOMENCLATURE		
PROVISIONING PRICE CODE		
PROVISIONING REMARKS		
QUANTITY PER ASSEMBLY (QPA)		
OPTION 1		
OPTION 2		
OPTION 3		
QUANTITY PER ASSEMBLY/QUANTITY PER END ITEM INDICATOR		
QUANTITY PER END ITEM (QPEI)		
OPTION 1		
OPTION 2		
OPTION 3		

FIGURE 2 - WORKSHEET 2 - LMI DATA PRODUCTS

**MIL-PRF-49506
APPENDIX B**

QUANTITY PER FIGURE		
QUANTITY PER TEST		
QUANTITY PER UNIT PACK		
QUANTITY PROCURED		
QUANTITY SHIPPED		
RECOMMENDED MINIMUM SYSTEM STOCK LEVEL		
RECURRING COST		
REFERENCE DESIGNATION		
OPTION 1		
OPTION 2		
OPTION 3		
OPTION 4		
OPTION 5		
REFERENCE DESIGNATION CODE (RDC)		
REFERENCE NUMBER		
REFERENCE NUMBER - AID		
REFERENCE NUMBER - ARN ITEM		
REFERENCE NUMBER - ARTICLES REQUIRING SUPPORT		
REFERENCE NUMBER - AUTOMATIC TEST EQUIPMENT		
REFERENCE NUMBER - CATEGORY III SE		
REFERENCE NUMBER - SUPPORT EQUIPMENT		
REFERENCE NUMBER - TPS		
REFERENCE NUMBER - UUT		
REFERENCE NUMBER (ARN) - ADDITIONAL		
REFERENCE NUMBER CATEGORY CODE (RNCC)		
REFERENCE NUMBER CATEGORY CODE - ARN		
REFERENCE NUMBER VARIATION CODE (RNVC)		
REFERENCE NUMBER VARIATION CODE - ARN		
REPAIR CYCLE TIME		
OPTION 1		
OPTION 2		

FIGURE 2 - WORKSHEET 2 - LMI DATA PRODUCTS

**MIL-PRF-49506
APPENDIX B**

REPLACED OR SUPERSEDING PROVISIONING LIST ITEM SEQUENCE NUMBER		
REPLACED OR SUPERSEDING PROVISIONING LIST ITEM SEQUENCE NUMBER INDICATOR (RS/IND)		
REPLACEMENT TASK DISTRIBUTION		
REVISION		
REVISION - SERD		
REWORK REMOVAL RATE (RRR)		
ROTATABLE POOL FACTOR (RPF)		
SAME AS PROVISIONING LIST ITEM SEQUENCE NUMBER (SAME AS PLISN)		
SCOPE		
SCOPE - DDCC		
SCOPE - IRCC		
SERIAL NUMBER EFFECTIVITY		
SERIAL NUMBER EFFECTIVITY - FROM		
SERIAL NUMBER EFFECTIVITY - TO		
SERVICE DESIGNATOR CODE (SER)		
SERVICE DESIGNATOR CODE - SE		
SERVICE DESIGNATOR CODE - USING		
SHELF LIFE (SL)		
SHELF LIFE ACTION CODE (SLAC)		
SKILL SPECIALTY CODE FOR SUPPORT EQUIPMENT OPERATOR		
SOURCE, MAINTENANCE AND RECOVERABILITY (SMR) CODE		
SOURCE, MAINTENANCE AND RECOVERABILITY CODE - SE		
SPARES ACQUISITION INTEGRATED WITH PRODUCTION (SAIP)		
SPECIAL MAINTENANCE ITEM CODE (SMIC)		
SPECIAL MARKING CODE		
SPECIAL MATERIAL CONTENT CODE (SMCC)		
SPECIAL PACKAGING INSTRUCTION NUMBER		
SPECIAL PACKAGING INSTRUCTION (SPI) NUMBER REVISION		

FIGURE 2 - WORKSHEET 2 - LMI DATA PRODUCTS

**MIL-PRF-49506
APPENDIX B**

SUPPLEMENTAL PACKAGING DATA		
SUPPORT EQUIPMENT DIMENSIONS		
SE DIMENSIONS OPERATING		
LENGTH		
WIDTH		
HEIGHT		
SE DIMENSIONS SHIPPING		
LENGTH		
WIDTH		
HEIGHT		
SE DIMENSIONS STORAGE		
LENGTH		
WIDTH		
HEIGHT		
SUPPORT EQUIPMENT EXPLANATION		
SUPPORT EQUIPMENT RECOMMENDATION DATA NUMBER (SERD NUMBER)		
SUPPORT EQUIPMENT RECOMMENDATION DATA REVISION/SUPERSEDURE REMARKS		
SUPPORT EQUIPMENT WEIGHT		
SUPPORT EQUIPMENT WEIGHT - OPERATING		
SUPPORT EQUIPMENT WEIGHT - SHIPPING		
SUPPORT EQUIPMENT WEIGHT - STORAGE		
TECHNICAL MANUAL CHANGE NUMBER (TM CHG)		
TECHNICAL MANUAL INDENTURE CODE (TM IND)		
TECHNICAL MANUAL NUMBER		
TEST ACCURACY RATIO (TAR)		
TEST ACCURACY RATIO - CATEGORY III SE		
TEST ACCURACY RATIO - UUT PARAMETER		
TOTAL ITEM CHANGES (TIC)		
TOTAL QUANTITY RECOMMENDED		
TYPE EQUIPMENT CODE		
TYPE OF CHANGE CODE (TOCC)		

FIGURE 2 - WORKSHEET 2 - LMI DATA PRODUCTS

MIL-PRF-49506
APPENDIX B

TYPE OF PRICE CODE		
TYPE OF STORAGE CODE		
UNIT CONTAINER CODE		
UNIT CONTAINER LEVEL		
UNIT OF ISSUE (UI)		
UNIT OF ISSUE CONVERSION FACTOR (UI CONVERSION FACTOR)		
UNIT OF ISSUE/UNIT OF MEASURE CODE		
UNIT OF ISSUE/UNIT OF MEASURE PRICE (UI/UM PRICE)		
UNIT OF MEASURE (UM)		
UNIT OF MEASURE - SE DIMENSIONS OPERATING		
UNIT OF MEASURE - SE WEIGHT OPERATING		
UNIT OF MEASURE - SE DIMENSIONS STORAGE		
UNIT OF MEASURE - SE WEIGHT STORAGE		
UNIT OF MEASURE - SE DIMENSIONS SHIPPING		
UNIT OF MEASURE - SE WEIGHT SHIPPING		
UNIT PACK CUBE		
UNIT SIZE		
UNIT SIZE - LENGTH		
UNIT SIZE - WIDTH		
UNIT SIZE - HEIGHT		
UNIT SIZE - PACK LENGTH		
UNIT SIZE - PACK WIDTH		
UNIT SIZE - PACK DEPTH		
UNIT UNDER TEST EXPLANATION		
UNIT WEIGHT		
UNIT WEIGHT - PACK		
USABLE ON CODE (UOC)		
USABLE ON CODE - DESIGN CHANGE		

FIGURE 2 - WORKSHEET 2 - LMI DATA PRODUCTS

MIL-PRF-49506
APPENDIX B

USABLE ON CODE - SUPPORT EQUIPMENT		
WEAROUT LIFE		
WORK UNIT CODE		
WORK UNIT CODE - ARTICLES REQUIRING SUPPORT		
WRAPPING MATERIAL		

FIGURE 2 - WORKSHEET 2 - LMI DATA PRODUCTS

MIL-PRF-49506
APPENDIX C

LIST OF LMI ACRONYMS

C.1 SCOPE

C.1.1 SCOPE. This appendix is used for listing acronyms used MIL-PRF-49506. This appendix is not mandatory.

C.2 ACRONYMS.

AFR	Air Force Regulation
AIC	Allowance Item Code
AID	Adaptor Interconnect Device
AIPC	Alternate Indentured Product Code
AMSDL	Acquisition Management Systems and Data Requirements Control List
APL	Allowance Part List
AR	Army Regulations
ARN	Additional Reference Number
ATE	Automatic Test Equipment
BDG	Brigade
BN	Battalion
BOI	Basis Of Issue
CAGE	Commercial and Government Entity
CBIL	Common and Bulk Item List
CFR	Code of Federal Regulations
CMRS	Calibrations Measurement Requirements Summary
COSAL	Coordinated Shipboard/Allowance List
CR	Contractor Recommended
CT	Cushioning Thickness
CTIC	Contractor Technical Information Code
DD	Data Dictionary
DDCC	Design Data Category Code
DIC	Document Identifier Code
DID	Data Item Description
DLSC	Defense Logistics Service Center
DOD	Department of Defense
DODISS	Department of Defense Index of Specifications and Standards
DPD	Data Product Definition
EIAC	End Item Acronym Code
ELIN	Exhibit Line Item Number
FAA	Federal Aviation Administration
FSC	Federal Supply Classification
GFE	Government Furnished Equipment
HQ	Headquarters
IAW	In Accordance With
ICC	Item Category Code
IEEE	Institute of Electrical and Electronics Engineers
ILS	Integrated Logistic Support
IMAC	Industrial Materials Analysis of Capacity
I/O	Input/Output
IPC	Indentured Product Code
IRCC	Integrated Logistic Support Requirement Category Code
ISL	Integrated Stock List
JETDS	Joint Electronics Type Designation System
LMI	Logistics Management Information
LRU	Line Replaceable Unit
MAM	Maintenance Assistance Modules
MAOT	Maximum Allowable Operating Time
MB	Measurement Base
MRF	Maintenance Replacement Factor
MRR1	Maintenance Replacement Rate I

MIL-PRF-49506

APPENDIX C

MRRII	Maintenance Replacement Rate II
MTBF	Mean Time Between Failures
MTD	Maintenance Task Distribution
MTTR	Mean Time To Repair
NATO	North Atlantic Treaty Organization
NHA	Next Higher Assembly
NI	Not Interchangeable
NIIN	National Item Identification Number
NSN	National Stock Number
OBRP	On Board Repair Part
O/M	Operations and Maintenance
ORR	Overhaul Replacement Rate
OTP	Operational Test Program
PCCN	Provisioning Contract Control Number
PLCC	Provisioning List Category Code
PLISN	Provisioning List Item Sequence Number
PLT	Production Lead Time
PMIC	Precious Metal Indicator Code
PMR	Planned Maintenance Requirements
PMS	Planned Maintenance System
PPL	Provisioning Parts List
QPA	Quantity Per Assembly
QPEI	Quantity Per End Item
QTY-AUTH	Quantity Authorized
RCT	Repair Cycle Time
RDC	Reference Designation Code
RNCC	Reference Number Category Code
RNVC	Reference Number Variation Code
RPF	Rotatable Pool Factor
RRR	Rework Removal Rate
R-S	Replaced or Superseding
RS/IND	Replaced or Superseding Provisioning List Item Sequence Number Indicator
RSS	Ready Service Spare
RTD	Replacement Task Distribution
R/V	Range/Value
SAIP	Spares Acquisition Integrated With Production
SAS	Supportability Analysis Summary
SE	Support Equipment
SER	Service Designator Code
SERD	Support Equipment Recommendation Data
SL	Shelf Life
SLAC	Shelf Life Action Code
SMCC	Special Material Content Code
SMIC	Special Maintenance Item Code
SMR	Source, Maintenance, and Recoverability Code
SNSL	Stock Number Sequence List
SPI	Special Packaging Instruction
SRA	Special Repair Activity
SRA	Shop Replaceable Assembly
SRU	Shop Replaceable Unit
SVC	Service Company
TAR	Test Accuracy Ratio
TIC	Total Item Changes
TM	Technical Manual
TM CHG	Technical Manual Change Number
TM CODE	Technical Manual Code
TMDE	Test, Measurement, and Diagnostic Equipment
TM IND	Technical Manual Indenture Code
TOCC	Type of Change Code
TOR	Technical Override
TPI	Test Program Instruction

MIL-PRF-49506
APPENDIX C

UI	Unit of Issue
UM	Unit of Measure
UOC	Usable On Code
UUT	Unit Under Test
WRA	Weapons Replaceable Assembly

1

1. **SCOPE**..... 1

1.1 Scope 1

2

2. **APPLICABLE DOCUMENTS** 2

2.1 General 2

2.2 Government documents 2

2.2.1 Specifications, standards, and handbooks 2

2.2.2 Other Government documents, drawings, and publications..... 2

2.3 Non-Government publications..... 3

2.4 Order of precedence 3

3

3. **REQUIREMENTS** 3

3.1 General 3

3.2 Product Requirements 3

3.2.1 Supportability Analysis Summaries..... 3

3.2.1.1 SAS Level of Detail..... 3

3.2.1.2 SAS Current Design Configuration 3

3.2.2 LMI Data Products 3

3.2.2.1 Data Product Level of Detail 4

3.2.2.2 Data Product Current Design Configuration..... 4

4

4. **VERIFICATION** 4

4.1 General 4

4.2 Supportability Analysis Summaries..... 4

4.2.1 SAS Level of Detail..... 4

4.2.2 SAS Accuracy Verification 4

4.3 LMI Data Products 4

4.3.1 Data Product Level of Detail 4

4.3.2 Data Product Accuracy Verification..... 4

5

5. **PACKAGING** 4

5.1 General 4

6

6. **NOTES**..... 4

6.1 Intended use..... 4

6.2 Issue of DODISS 4

6.3 Consideration of data requirements 4

6.4. Acronyms 5

6.5 Definitions 5

6.5.1 Assembly 5

6.5.2 Attaching part 5

6.5.3 Component 5

6.5.4 Contractor 5

6.5.5 Design Change..... 5

6.5.6 End Item 5

6.5.7 Hardware Breakdown 5

6.5.8 Part 5

6.5.9 Repair Part 5

6.5.10 Spares 6

6.5.11 Subassembly 6
 6.5.12 Support Equipment 6
 6.5.13 Support Items 6
 6.6 Subject term (key word) listing 6
 6.7 Guidance 6
 6.7.1 Data organization 6
 6.7.2 LMI Development 6
 6.8 Electronic Delivery of LMI 6

A

A.1 SCOPE - SUPPORTABILITY ANALYSIS SUMMARIES 8
 A.1.1 Scope 8
 A.2 Maintenance Planning 8
 A.3 Repair Analysis 8
 A.4 Support and Test Equipment 9
 A.5 Supply Support 9
 A.6 Manpower, Personnel, and Training 9
 A.7 Facilities 9
 A.8 Packaging, Handling, Storage, and Transportation 9
 A.9 Post Production Support 9

B

B.1 SCOPE - LMI DATA PRODUCT DICTIONARY 12
 B.1.1 Scope 12
 B.2 Sections 12
 B.2.1 Format 12
 B.2.2 Definition of terms 13
 B.2.2.1 DPD# 13
 B.2.2.2 Data title 13
 B.2.2.3 Field format 13
 B.2.2.4 Data Definition 13
 B.2.2.5 Data item 13
 B.2.2.6 Data code 13
 B.2.2.7 Associated name 14

C

C.1 SCOPE - ACRONYMS 74
 C.1.1 SCOPE 74
 C.2 ACRONYMS 74

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1,2,3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4,5,6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of this form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE	1.DOCUMENT NUMBER	2.DOCUMENT DATE (YYMMDD)
3.DOCUMENT TITLE LOGISTICS MANAGEMENT INFORMATION, MIL-PRF-49506		
4.NATURE OF CHANGE (<i>Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.</i>)		
5.REASON FOR RECOMMENDATION		
6.SUBMITTER		
a. NAME (<i>Last, First, Middle Initial</i>)	b. ORGANIZATION	
c. ADDRESS (<i>Include Zip Code</i>)	d. TELEPHONE (<i>Include Area Code</i>) (1)Commercial	7.DATE SUBMITTED (YYMMDD)
	(2)AUTOVON(<i>If applicable</i>)	
8.PREPARING ACTIVITY		
a.NAME USAMC Logistics Support Activity	b.TELEPHONE (<i>Include Area Code</i>) (1)Commercial (2)AUTOVON (205) 955-9837 645-9837	
c.ADDRESS (<i>Include Zip Code</i>) ATTN: AMXLS-ALD Redstone Arsenal, AL 35898-7466	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Commander
USAMC Logistics Support Activity
ATTN: AMXLS - ALD
Bldg 5307, Sparkman Circle
Redstone Arsenal, AL 35898-7466